



# MXH Heated Panel Formwork

Instructions for Assembly and Use – Standard Configuration – Issue 02/2018



## Main components



- A2 Panels
- A3 Panel connections
- A4 Tie technology
- B2 Push-Pull Props, Kickers
- B3 MAXIMO MXK Bracket System
- B5 Safety installations
- C2 Heating system – assembly

|                                       |    |  |    |
|---------------------------------------|----|--|----|
| <b>Overview</b>                       |    |  |    |
| Main components                       | 2  |  |    |
| Key                                   | 4  |  |    |
| Introduction                          |    |  |    |
| Target groups                         | 5  |  |    |
| Additional technical documentation    | 5  |  |    |
| Intended use                          | 6  |  |    |
| Cleaning and maintenance instructions | 7  |  |    |
| Periodic inspections                  | 7  |  |    |
| Safety instructions                   |    |  |    |
| Cross-system                          | 8  |  |    |
| System-specific                       | 9  |  |    |
| Storage and transportation            | 9  |  |    |
| General                               |    |  |    |
| A1 Storage and transportation         | 10 |  |    |
| Individual transport units            | 10 |  |    |
| A2 Panels                             |    |  |    |
| Panel sizes                           | 12 |  |    |
| Defining the building steps           | 12 |  |    |
| Panel overview                        | 13 |  |    |
| A3 Panel connections                  | 14 |  |    |
| Alignment Coupler BFD                 | 14 |  |    |
| Compensation Waler MAR 85             | 15 |  |    |
| Adaptor Connector MXH                 | 16 |  |    |
| A4 Tie technology                     | 17 |  |    |
| Tie systems                           | 17 |  |    |
| Scaffold Builder Ratchet Extension    | 17 |  |    |
| Tie Holder                            | 17 |  |    |
| <b>Assembly</b>                       |    |  |    |
| B1 Pre-assembly                       |    |  |    |
| Heated Panel                          | 18 |  |    |
| Height extensions                     |    |  |    |
| with Heated Formwork Panels           | 19 |  |    |
| with Panel MX 30                      | 20 |  |    |
| Connecting Heated Formwork Panels     | 21 |  |    |
| B2 Push-Pull Props                    |    |  |    |
| Connector RS MXH                      | 22 |  |    |
| Push-Pull Props and Kickers           | 22 |  |    |
| B3 MAXIMO MXK Bracket System          |    |  |    |
| Scaffold Bracket MXK                  | 23 |  |    |
| Scaffold Deck MXK                     | 24 |  |    |
| Scaffold Deck MXK with Access Hatch   | 25 |  |    |
| Guardrail Post MXK                    | 25 |  |    |
| B4 Erection                           | 26 |  |    |
| Moving with the crane                 | 26 |  |    |
| B5 Safety Installations               |    |  |    |
| Side Mesh Barrier PMB                 | 27 |  |    |
| Stepend Guardrail MXK                 | 27 |  |    |
| Access Ladder                         | 28 |  |    |
| Gap filling                           | 28 |  |    |
| B6 Additional Heated Panel Units      | 29 |  |    |
| Closing formwork                      | 29 |  |    |
| Tie Holder                            | 30 |  |    |
| <b>Electrical components</b>          |    |  |    |
| C1 Heating system - technical data    | 31 |  |    |
| Switch cabinet                        | 31 |  |    |
| Cables                                | 31 |  |    |
| Heating mat                           | 31 |  |    |
| C2 Heating system - assembly          | 32 |  |    |
| Switch cabinet                        | 32 |  |    |
| Cable connections                     | 33 |  |    |
| Establishing connections              | 34 |  |    |
| Connecting the site power supply      | 34 |  |    |
| C3 Heating control system             |    |  |    |
| Switching on the heating system       | 35 |  |    |
| Adjusting the temperature             | 35 |  |    |
| Switching off the heating system      | 35 |  |    |
| Troubleshooting                       | 36 |  |    |
| Striking / Dismantling                |    |  |    |
| D1 Moving Heated Panel Units          | 37 |  |    |
| Maximum transport units               | 37 |  |    |
| Moving with the crane                 | 38 |  |    |
| D2 Dismantling Heated Panel Units     | 39 |  |    |
| Disassembling Heated Panel Units      | 40 |  |    |
| Dismantling Heated Formwork Panels    | 40 |  |    |
| <b>Cleaning and maintenance</b>       |    |  |    |
| E1 Cleaning and maintenance           |    |  |    |
| Cleaning                              | 41 |  |    |
| Maintenance                           | 42 |  |    |
| Periodic inspections                  | 42 |  |    |
| Test Device MXH                       | 42 |  |    |
| <b>Appendix</b>                       |    |  |    |
| F1 Circuit diagrams                   | 44 |  |    |
| F2 Switch cabinet                     | 49 |  |    |
| F3 Components list                    | 52 |  |    |
| <b>Declaration of Conformity</b>      |    |  |    |
|                                       |    |  | 56 |
| <b>Data Sheet</b>                     |    |  |    |
| OMRON E5CB                            |    |  | 58 |
| <b>Components</b>                     |    |  |    |
| MXH Heated Formwork                   |    |  | 66 |

## Key

### Pictogram | Definition



Safety instructions



Note



Load-bearing point



Visual check



Hot surface



Safety gloves



Personal protective equipment to prevent falling from a height (PPE)



Misapplication

### Dimension specifications

Dimensions are usually given in mm. Other units of measure, e.g. cm, are specified in the illustrations.

Load details are usually given in kg. Other measurement units, e.g. t, are specified in the illustrations.

### Conventions

- Instructions are numbered with:  
1. ...., 2. ...., 3. ....
- The result of an instruction is shown by: →
- Position numbers are clearly provided for the individual components and are given in the drawing, e.g. **1**, in the text in brackets, for example (1).
- Multiple position numbers, i.e. alternative components, are represented with a slash, e.g. **1 / 2**.

### Arrows

- ➔ Arrow representing an action

## Presentational reference

The illustration on the front cover of these instructions is understood to be a system representation only. The assembly steps presented in these Instructions for Assembly and Use are shown in the form of examples with only one component size. They are valid accordingly for all component sizes contained in the standard configuration.

For a better understanding, detailed illustrations are partly incomplete. The safety installations which have possibly not been included in these detailed drawings must nevertheless still be available.

## Target groups

### Contractors

These Instructions for Assembly and Use are designed for contractors who either

- assemble, modify and dismantle the formwork system, or
- use it, e.g. for concreting, or
- allow it to be used for other work operations, e.g. carpentry or electrical work.

### Construction site coordinator

The Safety and Health Protection Coordinator\*

- is appointed by the client,
- must identify potential hazards during the planning phase,
- determines measures that provide protection against risks,
- creates a safety and health plan,
- coordinates the protective measures for the contractor and site personnel so that they do not endanger each other,
- monitors compliance with the protective measures.

### Competent persons

Due to the specialist knowledge gained from professional training, work experience, and recent professional activity, the competent person has a reliable understanding of safety-related issues and can correctly carry out inspections.

Depending on the complexity of the test to be undertaken, e.g. scope of testing, type of testing or the use of a certain measuring device, a range of specialist knowledge is necessary.

### Qualified persons

Formwork systems may only be assembled, modified or dismantled by personnel who are suitably qualified to do so. For the work to be carried out, the qualified persons must have received instructions\*\* covering at least the following points:

- Explanation of the plan for the assembly, modification or dismantling of the formwork in an understandable form and language.
- Description of the measures for assembling, modifying or dismantling the formwork.
- Designation of the preventive measures to avoid the risk of persons and objects falling.

- Designation of the safety precautions in the event of changing weather conditions which could adversely affect the safety of the formwork system as well as the persons concerned.
- Details regarding the permissible loads.
- Description of any other risks that are associated with the assembly, modification or dismantling procedures.



**In other countries, ensure that the relevant national guidelines and regulations in the respective current version are complied with!**

\* Valid in Germany: Regulations for Occupational Health and Safety on Construction Sites 30 (RAB 30)

\*\* Instructions are given by the contractor himself or a competent person selected by him.

---

## Additional technical documentation

- Instructions for Assembly and Use:
  - MAXIMO MX 15
  - MAXIMO MX 18
  - MAXIMO MXK Bracket System
- Instructions for Use:
  - Instructions for Use: Lifting Gear "Combi" MX
  - Instructions for Use: Lifting Hook MAXIMO 1.5 t
  - Instructions for Use: Test Device MXH
- PERI Design Tables - Formwork and Shoring
- Technical Data Sheet for Anchor Bolt PERI 14/20 x 130

## Intended use

### Product description

PERI products have been designed for exclusive use in the industrial and commercial sectors by qualified personnel only.

MAXIMO MXH combines the MAXIMO Wall Formwork System with the MXH Heated Formwork.

The heating prevents the temperature of the concrete from falling when the outside temperature is low. This allows the hydration process to take place.

### Technical data

#### Power supply:

3-phase alternating current 400 V / 50 – 60 Hz

Connected load max. 7,200 W

Maximum current consumption 12.5 A

#### Connection

CEE plug 400 V, 16 A, 6h

#### Main switch

3-phase, mechanical separation (62) +N

#### Safeguards

3 x 16 A, Tripping Characteristic B (69)

3-phase residual-current protection device 25 A (68)

Conventional tripping current 30 mA

---

## Instructions on use

The use in a way not intended according to the Instructions for Assembly and Use, or any use deviating from the standard configuration or the intended use represents a misapplication with a potential safety risk, e.g. risk of falling.

Only PERI original parts may be used. The use of other products and spare parts is not allowed.

Changes to PERI components are not permitted.

## Cleaning and maintenance instructions

In order to maintain the value and operational readiness of the formwork materials over the long term, clean the panels after each use.

Some repair work may also be inevitable due to the tough working conditions. The following points should help to keep cleaning and maintenance costs as low as possible.

Do not spray release agent on the frame parts but spread by means of a cloth. This allows easier and faster cleaning of the formwork. Apply the concrete release agent very thinly and evenly! Ensure that the release agent does not come into contact with heating wires, cables, support fabric and insulating foam.

Spray the rear side of the formwork with water immediately after concreting; this avoids any time-consuming and costly cleaning operations.

When used continuously, clean the panel formlining immediately after striking using a scraper, brush or rubber lip scraper. Important: do not clean the heating elements with high-pressure equipment; this could damage the electrical installations.

Do not drill into, saw or nail the heating elements.

Close all unused tie holes with plugs; this eliminates any subsequent cleaning or repair work. Tie holes accidentally blocked with concrete are freed by means of a steel pin from the rear side.

Do not store anything on the heating elements.

Never clean powder-coated components, e.g. panels and accessories, with a steel brush or hard metal scraper; this ensures that the powder-coating remains intact.

Mechanical components, e.g. spindles or gear mechanisms, must be cleaned of dirt or concrete residue before and after use, and then greased with a suitable lubricant.

Provide suitable support for the components during cleaning so that no unintentional change in their position is possible.

Do not clean components suspended on crane slings.

## Periodic inspections

All electrical components of the MXH Heated Formwork have been inspected and furnished with an inspection plate according to the DGUV (German Statutory Accident Insurance).

The inspection plate indicates the month and date of the last inspection.

An insulation test, protective conductor test, and a working current measurement of the whole MXH Heated Formwork is to be carried out by a qualified electrician annually.

In addition, all relevant national provisions must be complied with.



## Cross-system

### General

The contractor must ensure that the Instructions for Assembly and Use supplied by PERI are available at all times and understood by the site personnel.

These Instructions for Assembly and Use can be used as the basis for creating a risk assessment. The risk assessment is compiled by the contractor. These Instructions for Assembly and Use do not replace the risk assessment!

Always take into consideration and comply with the safety instructions and permissible loads.

For the application and inspection of PERI products, observe the current safety regulations and guidelines applicable in the respective countries where the products are being used.

Materials and working areas are to be inspected on a regular basis, especially before each use and assembly, for:

- signs of damage,
- stability and
- function.

Damaged components must be exchanged immediately on site and may no longer be used.

Safety components are to be removed only when they are no longer required.

Components provided by the contractor must conform with the characteristics required in these Instructions for Assembly and Use as well as with all valid construction guidelines and standards. In particular, the following applies if nothing else is specified:

- Timber components: Strength Class C24 for Solid Wood according to EN 338.
- Scaffold tubes: galvanised steel tubes with minimum dimensions of  $\text{Ø } 48.3 \times 3.2 \text{ mm}$  according to EN 12811-1:2003 4.2.1.2.
- Scaffold tube couplings according to EN 74.

Deviations from the standard configuration are only permitted after a further risk assessment has been carried out by the contractor. On the basis of this risk assessment, appropriate measures for working and operational safety as well as stability are to be determined.

Corresponding proof of stability can be provided by PERI on request if the risk assessment and resulting measures to be implemented are made available.

Before and after exceptional occurrences that may have an adverse effect regarding the safety of the formwork system, the contractor must immediately

- create another risk assessment, with appropriate measures for ensuring the stability of the formwork system being carried out based on the results,
- and arrange for an extraordinary inspection by a competent person. The aim of this inspection is to identify and rectify any damage in good time in order to guarantee the safe use of the formwork system.

Exceptional occurrences can include:

- accidents,
- longer periods of non-use,
- natural events, e.g. heavy rainfall, icing, heavy snowfall, storms or earthquakes.

### Assembly, modification and dismantling work

Assembly, modification or dismantling of formwork systems may only be carried out by qualified persons and under the supervision of a competent person. The qualified persons must have received appropriate training for the work to be carried out with regard to specific risks and dangers.

On the basis of the risk assessment and the Instructions for Assembly and Use, the contractor must create installation instructions in order to ensure safe assembly, modification and dismantling of the formwork system.

The contractor must ensure that the personal protective equipment required for the assembly, modification or dismantling of the system, e.g.

- safety helmet,
  - safety shoes,
  - safety gloves,
  - safety glasses,
- is available and used as intended.

If personal protective equipment against falling from a height (PPE) is required or specified in local regulations, the contractor must determine appropriate attachment points on the basis of the risk assessment.

The PPE against falling to be used is determined by the contractor.

The contractor must

- provide safe working areas for site personnel which are to be reached through the provision of safe access ways. Areas of risk must be cordoned off and clearly marked.
- ensure the stability during all stages of construction, in particular during assembly, modification and dismantling of the formwork.
- ensure and prove that all loads can be safely transferred.

### Utilization

Every contractor who uses or allows formwork systems or sections of the formwork to be used, has the responsibility for ensuring that the equipment is in good condition.

If the formwork system is used successively or at the same time by several contractors, the health and safety coordinator must point out any possible mutual hazards and all work must be then coordinated.



## System-specific

Only operate heated panels in connection with assembled panel formwork.

Do not remove heating mats, do not use for heating rooms, vehicles or other unintended purposes.

Do not use the MXH Heated Formwork to defrost, heat or dry materials, clothing, textiles, food or other items for which it is not intended.

Heating wire and frame parts can become very hot. Do not touch during operations, allow to cool down before dismantling! Wear protective gloves.

Do not make any changes to the electrical equipment.

Only open the switch cabinet using the switch cabinet door. Do not remove the inside electric shock protection cover.

Do not mechanically load the heating mats.

Disconnect the power supply to the heater before assembly, dismantling and cleaning.

Do not clean the heating elements, cables and switch cabinet with a high-pressure cleaner.

Clean the heating mats with a damp cloth only, and protect against standing water.

Start operations only if the heating mats are completely dry.

Do not operate damaged parts. Repairs to the electrical system are to be carried out only by a qualified electrician authorised in accordance with respective national laws and regulations.

Do not store any flammable substances or objects in the vicinity during working operations.

Do not connect or operate in potentially explosive atmospheres.

Never bring insulating foam, heating mats and heating wires into contact with flammable substances.

The heated panels can be used as assembly aids when assembling mounting parts. However, ensure that they are not subjected to any loads.

## Storage and transportation

Store and transport components ensuring that no unintentional change in their position is possible. Detach lifting accessories and slings from the lowered components only if they are in a stable position and no unintentional change is possible.

Do not drop the components.

Use PERI lifting accessories and lifting gear as well as only those load-bearing points provided on the component.

During the moving procedure

- ensure that components are picked up and set down so that unintentional falling over, falling apart, sliding, falling down or rolling is avoided.
- no persons are allowed to remain under the suspended load.

The access areas on the jobsite must be free of obstacles and tripping hazards as well as being slip-resistant.

For transportation, the surface used must have sufficient load-bearing capacity.

Use original PERI storage and transport systems, e.g. pallet cages, pallets or stacking devices.

# A1 Storage and transportation



- For reasons of safety, panels should never be treated with a concrete release agent before transportation.
- Transportation units must be correctly stacked and secured!
- Only panels of the same size are to be transported in one stack!

## Individual transport units

Individual transport units are not suitable for transport by crane.

Place Heated Panels on a pallet (9) and secure with a sufficient number of steel bands (7).

Also secure pallets with steel bands. Stack floor bracket alternately right / left.

Insert anti-slip mats (8) between the steel frames. Use edge protection.




Fig. A1.01

## Heated Panels:

|                               |    |
|-------------------------------|----|
| MXH 270 x 240 cm (Fig. A1.01) | 5x |
| MXH 270 x 120 cm              | 5x |

Stack Heated Panels 270 x 120 cm on two Euro pallets.

## Heated Panel with assembled Panel Formwork MX:

|                               |    |
|-------------------------------|----|
| MXH 270 x 240 cm              | 4x |
| MXH 270 x 120 cm (Fig. A1.02) | 4x |

Stack Panel Formwork MX downwards, stack top panel with Panel Formwork MX upwards.




Fig. A1.02

# A1 Storage and transportation

Place Heated Panels on a Euro pallet (9) and secure with a sufficient number of steel bands (7). Also secure pallets with steel bands.

Insert anti-slip mats (8) between the steel frames. Use edge protection.

## Extension Heated Panels:

|                              |     |
|------------------------------|-----|
| MXH 120 x 240 cm             | 7x  |
| MXH 120 x 120 cm             | 7x  |
| MXH 60 x 240 cm (Fig. A1.03) | 14x |
| MXH 60 x 120 cm              | 14x |

2 stacks of MXH 60 are positioned next to each other, both sides have the same height! (Fig. A1.03)




Fig. A1.03

## Extension Heated Panels with assembled Panel Formwork MX:

|                               |    |
|-------------------------------|----|
| MXH 120 x 240 cm              | 4x |
| MXH 120 x 120 cm (Fig. A1.04) | 4x |
| MXH 60 x 240 cm               | 8x |
| MXH 60 x 120 cm               | 8x |

2 stacks of MXH 60 are positioned next to each other, both sides have the same height!

Stack Panel Formwork MX downwards, stack top panel with Panel Formwork MX upwards.




Fig. A1.04

## Panel sizes

Standard Heated Panel MXH

- 10** 270 x 240 cm
- 11** 270 x 120 cm

Extension Heated Panel MXH

- 12** 120 x 240 cm
- 13** 120 x 120 cm
- 14** 60 x 240 cm
- 15** 60 x 120 cm

Height Extension Panels MX without heating

- 16** 30 x 240 cm
- 17** 30 x 120 cm




Fig. A2.01

## Defining the building steps

### Panel

Individual, non-assembled panels:  
Heated Panel MXH (Fig. A2.02)  
Panel MX (Fig. A2.03)




Fig. A2.02




Fig. A2.03

### Heated Formwork Panel

Assembled Heated Formwork Panel consisting of Heated Panel MXH and Panel MX. (Fig. A2.04)




Fig. A2.04




Fig. A2.05

### Heated Formwork Unit

Assembled Heated Formwork Unit consisting of two or more Heated Formwork Panels. (Fig. A2.05)

### MXH Heated Formwork

Erected Heated Formwork Units. (Fig. A2.06)




Fig. A2.06

## Panel overview

### Rear side of Heated Panel MXH

- 10.1** Frame
- 10.2** Load-bearing point for crane eye
- 10.3 Panel strut
- 10.4** Cover plate
- 10.5** Installation angle\*
- 10.6** Anchor point
- 10.7** Electric connection socket
- 10.9** Transport opening, e.g. for Lifting Gear Combi

### Connection points for

- 20** Alignment Coupler BFD
- 21** Compensation Waler MAR\*
- 22** Connector RS MXH\*
- 23** Switch cabinet\*
- 24** Tie Holder\*
- 25** Scaffold Bracket\*
- 26** Ladder Connector\*

### Heating side of the Heated Panel MXH

- 10.8** Screw-on Locking Angle
- 82** Heating mat
- 84** Insulation (covered)

\* Not available on all panels.




Fig. A2.07




Fig. A2.08

### MXH Heated Formwork

Instructions for Assembly and Use – Standard Configuration

## Alignment Coupler BFD

(Fig. A3.01)

### Areas of use:

- Standard Heated Panel joints
- Extensions with Heated Panels.
- Extensions with Panel MX 30, in connection with Adaptor Connector MXH.

### Number of alignment couplers per standard panel joint

3x Alignment Coupler BFD (30) for H = 2.70 m. (Fig. A3.02)

### Assembly

1. Place wedge in upper end position.
2. Open sliding part. (Fig. A3.03)
3. Place Alignment Coupler BFD on the panel strut. (Fig. A3.04)
4. Close sliding part.
5. Hammer in wedge tightly. (Fig. A3.05)



If the wedge head rests on the sliding part, there is no clamping effect! (Fig. A3.06)

In this case: release wedge, re-position the sliding part and secure once again with the hammer.



When securing the wedge, the following effects occur due to the angle of the frame profile:

- 1. Panels are flush.
- 2. Panels are aligned.
- 3. Panels are tightly connected.

### Arrangement of the Alignment Couplers

see B1 Assembly, B6 Additional Heated Panel Units.




Fig. A3.01

Fig. A3.02




Fig. A3.03




Fig. A3.04




Fig. A3.05




Fig. A3.06

## Compensation Waler MAR 85

(Fig. A3.07)

The Compensation Waler MAR (31) has a triple function as a panel connection: to brace, align, and transfer forces.

### Areas of use:

- Standard Heated Panel joint (Fig. A3.08)

### Assembly

1. Release Nut (31.2), pull out Hook Tie towards the rear.
2. Insert hooks (31.1) in the connecting holes (21) of the panel. (Fig. A3.09)
3. Tighten Nut (31.2). (Fig. A3.10)




Fig. A3.07




Fig. A3.08




Fig. A3.09




Fig. A3.10

## Adaptor Connector MXH

(Fig. A3.11)

In conjunction with the Alignment Coupler BFD, the Adaptor Connector MXH is used for extending Panel MX 30.

### Areas of use:

- Extensions with Panel MX 30.

### Assembly

1. Insert claws of the Adapter Connection MXH (38) in the panel strut (16.3) of the Panel MX 30 (16). (Fig. A3.12)
2. Place Alignment Coupler BFD (30) on the panel strut (10.3) and Adaptor Connector MXH. (Fig. A3.13)
3. Close sliding part of the Alignment Coupler BFD.
4. Hammer in wedge tightly. (Fig. A3.14)




Fig. A3.11




Fig. A3.12




Fig. A3.13




Fig. A3.14



# A4 Tie technology

## Tie systems

The MX 15 and MX 18 Tie Systems are used.

The tie system consists of:  
MX 15 Tie (40) and Counterplate (41).  
(Fig. A4.01 + A4.02)




Fig. A4.01




Fig. A4.02

## Permissible tension force of the tie rods:

MX 18 130 kN  
MX 15 90 kN

## Assembly

The Heated Panels have access openings to the anchor points of the MAXIMO MX 15 and MX 18 Panel Formwork.  
(Fig. A4.03 + A4.04)

Assembly is carried out in the same way as for the MAXIMO MX 15 or MX 18 Panel Formwork, see Instructions for Assembly and Use for the MAXIMO MX 15 or MX 18.




Fig. A4.03




Fig. A4.04

## Scaffold Builder Ratchet Extension

If MX Ties are set to their maximum length, a Scaffold Builder Ratchet Extension (43) is required to tighten and loosen the MX Ties. (Fig. A4.05)




Fig. A4.05

## Tie Holder

The Tie Holder (44) is used for reliably storing MX Ties when moving the Heated Panels. (Fig. A4.06 + A4.07)

Assembly: see B6 Additional Heated Panel Units, Tie Holder.




Fig. A4.06




Fig. A4.07

## MXH Heated Formwork

Instructions for Assembly and Use – Standard Configuration

## Heated Formwork Panel



- **Danger due to suspended load!**
- **Take into account the permissible load-bearing capacity of the crane lifting gear and the crane capacity!**
- **Follow Instructions for Use for the Lifting Gear Combi MX at all times!**
- **Risk of crushing! During assembly, ensure that the panel cannot fall off or slide. Use stable supports!**
- **Risk of slipping! Heated Panels are slippery to handle in wet or snowy conditions. Do not walk on Heated Panels!**
- **Before assembly, inspect heating mats for any loose or broken heating wires. Do not use damaged Heated Panels.**



Pay attention to the alignment! Openings for anchors and anchor bolt must match.

Heated Panels MXH are always assembled on the Panel MX in the same way regardless of the panel size.

Only mount Heated Panel MXH on Panel Formwork MAXIMO MX of the same size.

### Required components:

|           |                     |   |
|-----------|---------------------|---|
| <b>10</b> | Heated Panel MXH    | 1 |
| <b>18</b> | Panel MX            | 1 |
| <b>37</b> | Fixing Bolt M14 MXH | 8 |

### Assembly

1. Lay out timber (9) or planking as a base. The assembly area must be even.
2. Place Panel MX (18) with formlining facing downwards on the supports.
3. Attach the Heated Panel MXH (10) with the Lifting Gear Combi MX (3) to the transport openings (10.9) and then place this on the Panel MX using the crane. (Fig. B1.01)
4. At each of the 4 corners, insert 2x Fixing Bolts M14 MXH (37) through the openings of the Panel MX into the Screw-On Locking Angle (10.8) and tighten. Wrench size: Allen Key SW 10. (Fig. B1.02)




Fig. B1.01




Fig. B1.02

## Height extensions

Heated Formwork Panels are pre-assembled horizontally to form Heated Panel Units.

Height max. = 4.00 m.



Maximum transport units: see D1 Moving Heated Panel Units.

### Permissible combinations

for panel widths 1.20 m and 2.40 m:

- MXH 270,
  - MXH 270 + MX 30,
  - MXH 270 + MXH 60,
  - MXH 270 + MXH 60 + MX 30,
  - MXH 270 + MXH 120.
- (Fig. B1.03)

### Extensions with Heated Formwork Panels

#### Required components:

For panel widths 2.40 m

|           |   |    |
|-----------|---|----|
| <b>10</b> | Heated Formwork Panel<br>270 x 240              | 1x |
| <b>12</b> | Extension Heated Formwork Panel<br>120 x 240 or |    |
| <b>14</b> | 60 x 240  | 1x |
| <b>30</b> | Alignment Coupler BFD                           | 4x |

For panel widths 1.20 m.

|           |   |    |
|-----------|---|----|
| <b>10</b> | Heated Formwork Panel<br>270 x 120              | 1x |
| <b>13</b> | Extension Heated Formwork Panel<br>120 x 120 or |    |
| <b>15</b> | 60 x 120  | 1x |
| <b>30</b> | Alignment Coupler BFD                           | 2x |

#### Assembly

1. Lay out timber (9) or planking as a base. The assembly area must be even.
2. Place Heated Formwork Panel (10) with formlining facing downwards on the supports. (Fig. B1.04)
3. Position the Extension Heated Formwork Panel (12) at the top. (Fig. B1.05)
4. Connect the Heated Formwork Panel to the designated frame struts using the Alignment Coupler BFD (30). (Fig. B1.06 + B1.06a)  
See A3 Panel connections.  
→ Heated Formwork Unit is now mounted.




Fig. B1.03




Fig. B1.04




Fig. B1.05




Fig. B1.06




Fig. B1.06a

## Extensions with Panel MX 30



- **Danger due to suspended load!**
- **Take into account the permissible load-bearing capacity of the crane lifting gear and the crane capacity!**
- **Follow Instructions for Use for the Lifting Gear Combi MX at all times!**

Use the Adapter Connector MXH (38) for connecting Panel MX 30 to a Heated Formwork Panel. (Fig. B1.07)

### Required components:

For panel widths 2.40 m

|           |                                      |    |
|-----------|--------------------------------------|----|
| <b>10</b> | Heated Formwork Panel<br>270 x 240   | 1x |
| <b>12</b> | Extension Heated Formwork<br>Panel * | 1x |
| <b>16</b> | Panel MX 30 x 240                    | 1x |
| <b>38</b> | Adaptor Connector MXH                | 4x |
| <b>30</b> | Alignment Coupler BFD                | 4x |

For panel widths 1.20 m.

|           |                                      |    |
|-----------|--------------------------------------|----|
| <b>10</b> | Heated Formwork Panel<br>270 x 120   | 1x |
| <b>13</b> | Extension Heated Formwork<br>Panel * | 1x |
| <b>17</b> | Panel MX 30 x 120                    | 1x |
| <b>38</b> | Adaptor Connector MXH                | 2x |
| <b>30</b> | Alignment Coupler BFD                | 2x |

\*Depending on the selected combination.

### Assembly

1. Position Panel MX 30 (17) on the Heated Formwork Panel (10) or Extension Heated Formwork Panel at the top. (Fig. B1.08)
2. Attach Adapter Connector MXH (38) to the frame strut in Panel MX 30 with the claws. Adapter Connector MXH is positioned on the top edge of the Heated Formwork Panel. (Fig. B1.09)
3. Connect the Heated Formwork Panel MXH and Panel MX 30 to the frame strut and Adapter Connector MXH using the Alignment Coupler BFD (30). (Fig. B1.10)  
See A3 Panel connections.




Fig. B1.07




Fig. B1.08




Fig. B1.09




Fig. B1.10




Fig. B1.11

## Connecting Heated Formwork Panels

Heated Formwork Panels can be pre-assembled horizontally to form larger Heated Panel Units.



Maximum transport units: see D1 Moving Heated Panel Units.

Required number of Alignment Coupler BFD and Compensation Waler MAR 85:

### Vertical joints

|                     |                       |
|---------------------|-----------------------|
| Panel height 2.70 m | 3 x BFD<br>1 x MAR 85 |
| Panel height 1.20 m | 2 x BFD               |
| Panel height 0.60 m | 1 x BFD               |
| Panel height 0.30 m | –                     |

### Horizontal joints

|                    |         |
|--------------------|---------|
| Panel width 2.40 m | 4 x BFD |
| Panel width 1.20 m | 2 x BFD |

### Assembly

1. Lay out timber or planking as a base. The assembly area must be even.
2. Place Heated Formwork Panels with formlining facing downwards on the supports.
3. Connect the Heated Formwork Panels to the designated frame struts using the Alignment Couplers BFD (30) and Compensation Walers MAR 85 (31). (Fig. B1.12 + B1.13)  
See A3 Panel connections.
4. If required, mount additional Heated Formwork Panels.  
→ Heated Formwork Panel Units are now mounted.



Install Compensation Waler MAR 85 offset if the adjacent Heated Formwork Panel is 1.20 m wide and a switch cabinet is to be installed there. (Fig. B1.13)




Fig. B1.12




Fig. B1.13

# B2 Push-Pull Props



## Connector RS MXH



– **Risk of slipping! Heated Panels are slippery to handle in wet or snowy conditions. Do not walk on Heated Panels!**

Push-pull props and Kickers are attached to the panel using the Connector RS MXH. If required, wind bracing can be attached to the Connector RS MXH. (Fig. B2.01a)

### Assembly

1. Release Triple Wingnut (32.2) and pull back Hook Tie (32.1).
2. Position the Connector RS MXH (32) on the panel strut (22) so that the Hook Tie (32.1) is linked into a connecting hole. (Fig. B2.02)
3. Tighten Connector RS MXH with the Triple Wingnut (32.2). (Fig. B2.03)  
→ Connector RS MXH is now mounted. (Fig. B2.04)





Fig. B2.01



An alternative Connector RS MXH




Fig. B2.01a




Fig. B2.02




Fig. B2.03

## Push-Pull Props and Kickers

### Required components:

|           |                       |           |    |
|-----------|-----------------------|-----------|----|
| <b>10</b> | Heated Formwork Panel | 270 x 240 | 1x |
| <b>32</b> | Connector RS MXH      |           | 4x |
| <b>90</b> | Push-Pull Prop        |           | 2x |
| <b>91</b> | Kicker                |           | 2x |
| <b>92</b> | Base Plate            |           | 2x |



Push-Pull Props and Kickers are mounted in order to align the formwork as well as providing stability. The choice of the Push-Pull Prop and Kicker is determined by the height of the formwork. The maximum width of influence is 2.40 m. Observe design table for PERI Push-Pull Props and Kickers.

### Assembly

1. Fix Push-Pull Prop (90) and Kicker (91) to the connecting eyelet (32.4) of the Connector RS MXH (32) by means of bolts and cotter pins.
2. Connect Push-Pull Prop and Kicker to the Base Plate (92). (Fig. B2.05)  
→ Push-Pull Props are now mounted.




Fig. B2.04




Fig. B2.05



Is the cotter pin correctly positioned?



- **Risk of crushing!** During assembly, ensure that the panel cannot fall off or slide. Use stable supports!
- **Risk of slipping!** Heated Panels are slippery to handle in wet or snowy conditions. Do not walk on Heated Panels!
- **Follow Instructions for Assembly and Use for the MAXIMO MXK Bracket System!**



Assembly of the MXK Bracket System takes place on horizontally-positioned panels. See Instructions for Assembly and Use for the MAXIMO MXK Bracket System.




Fig. B3.01




Fig. B3.02

## Scaffold Bracket MXK

### Assembly

1. Push the Scaffold Bracket MXK (50) with the top and bottom Connector RS MXH from above into the connection hole for scaffold brackets (25). (Fig. B3.01)
2. The Scaffold Bracket is correctly positioned if the hooks (50.3) of the securing pin are positioned as shown in Fig. B3.02.



Visual and functional check! The hook (50.3) of the securing pin must be held in position with spring force. (Fig. B3.02)

If the spring force is missing, the Scaffold Bracket MXK must not be used!

## Scaffold Deck MXK

### Assembly

1. Position both guide bolts (51.1) of the Scaffold Deck MXK (51) behind the plates (50.6) of the Scaffold Brackets MXK (50). (Fig. B3.04 + B3.04a)
2. Press the Scaffold Deck MXK to the Scaffold Bracket MXK.
3. Lift the Scaffold Deck MXK over the retaining bolts (50.7), press to the Bracket and lower. (Fig. B3.05) → Scaffold Deck MXK is now mounted.
4. Scaffold Deck MXK is secured by assembling the Guardrail Post MXK.




Fig. B3.03



Both hooks (51.2) of the Scaffold Deck MXK must be hooked in on both sides above the retaining bolts (50.7). (Fig. B3.05)



**Risk of injury from falling components!**  
If Guardrail Post MXK has not been mounted, the Heated Formwork Unit may not be placed in position.




Fig. B3.04




Fig. B3.04a




Fig. B3.05



## Scaffold Deck MXK with Access Hatch

When assembling the Scaffold Deck with Access Hatch (53) and Access Ladder, make sure that these are not mounted on the left-hand unit in order to ensure free access to the switch cabinet.

The electrical switch cabinet is always installed on the left of max. 3 Heated Panels.

The Scaffold Deck with Access Hatch is mounted in the same way as the Scaffold Deck MXK.

### Access Ladder

is mounted on a vertically-positioned panel, see B5 Safety installations.




Fig. B3.06

## Guardrail Post MXK

### Assembly

Push the Guardrail Posts MXK (52) into the support (50.4) of the Scaffold Bracket MXK until the securing hook (52.1) locks into the hole (50.5) (Fig. B3.08) → Guardrail Post MXK is now secured.  
→ Scaffold Deck MXK is now secured.




Fig. B3.07




Fig. B3.08

For assembly of other decks, see Instructions for Assembly and Use for the MAXIMO MXK Bracket System.



The securing hook must be held in position with spring force. (Fig. B3.08) If the spring force is missing, the Guardrail Post MXK must not be used!

Mount Side Mesh Barrier PMB, Stopped Guardrail MXK and Access Ladder after erection.



**Risk of falling! When using the MXK Bracket System with incomplete guardrails, measures to prevent falling must be taken!**




Fig. B3.09

## Moving with the crane



- Risk of falling! Fall protection measures, e.g. PPE against falls from a height, are to be implemented if persons work on the Scaffold Bracket System MXK without a fully-mounted guardrail.
- Danger due to suspended load!
- Take into account the permissible load-bearing capacity of the crane lifting gear and the crane capacity!
- Follow Instructions for Use for Lifting Gear Combi MX and Lifting Hook MAXIMO 1.5 t!



- For working areas at great heights choose a safe working area, e.g. mobile scaffold.
- Maximum transport units see D1 Moving Heated Panel Units.

### Heated Panel MXH

Move Heated Panel Unit using the load-bearing point of the Crane Eye (10.2). (Fig. B4.01)

### Panel MX 30

Use Lifting Hook MAXIMO 1.5 t (4) for Heated Panel Units with Panel MX 30 as extension. (Fig. B4.01a)

### Assembly

1. Attach Combi Lifting Gear to the load-bearing point of the Crane Eye (10.2) or Lifting Hook (4). (Fig. B4.01 + B4.01a)
2. Transport panel to place of operation by crane.
3. Mount Base Plate (92), e.g. with PERI Anchor Bolt 14/20 x 130 (93) (Fig. B4.03 + B4.03a)
4. Using PPE to prevent falling from a height, mount Side Mesh Barrier PMB and Stopend Guardrail MXK, see B5 Safety installations.
5. Release Combi Lifting Gear from the load-bearing point of the Crane Eye or Lifting Hook.



When using PERI Anchor Bolt 14/20 x 130, take into account the Technical Data Sheet!




Fig. B4.01




Fig. B4.01a




Fig. B4.02




Fig. B4.03




Fig. B4.03a



- Risk of falling! Fall protection measures, e.g. PPE to prevent falling from a height, are to be implemented if work is carried out on the Scaffold Bracket System MXK without fully-mounted guardrails.
- Follow Instructions for Assembly and Use for the MAXIMO MXK Bracket System!

## Side Mesh Barrier PMB

### Assembly

1. Hook Side Mesh Barriers PMB 120 (54) into the top L-bracket (52.2).
  2. The Toeboard is held in position.
  3. Lift the adjustable L-bracket (52.3). (Fig. B5.01)
  4. Push Toeboard to the Guardrail Post Holder MXK. (Fig. B5.01)
  5. Lower the adjustable L-bracket (52.3). (Fig. B5.02)
- Side Mesh Barrier PMB is now secured against lifting.




Fig. B5.01




Fig. B5.02

## Stopend Guardrail MXK

### Assembly

1. Release wedges (55.1) of the Stopend Guardrail MXK (55).
  2. Fix locking bolt (55.4) on the centre of the bracket. (Fig. B5.03 + B5.03a)
  3. Place Stopend Guardrail MXK on the Guardrail Post MXK (52). (Fig. B5.03 + B5.03a)
  4. The mounting (55.2) must rest on the Scaffold Deck. (Fig. B5.03a)
  5. Position support (55.3) of the Stopend Guardrail MXK on the centre of Bracket MXK.
  6. Stopend Guardrail is secured by striking both wedges on the Guardrail Post MXK (52) with a hammer. (Fig. B5.04)
- Stopend Guardrail MXK is now mounted. (Fig. B5.05)




Fig. B5.03




Fig. B5.03a




Fig. B5.04




Fig. B5.05

## Access Ladder

### Assembly

1. Release Triple Wingnut (56.1) on the Ladder Connector (56) and pull out Hook Tie (56.2) towards the rear.
2. Place Ladder Connector on the panel strut (26) so that the Hook Tie (56.2) engages the connecting hole.
3. Tighten the Ladder Connector using the Triple Wingnut (56.1). (Fig. B5.07)
4. Remove tube linch pin (56.3) from the Ladder Connector. (Fig. B5.08)
5. Attach the Ladder to the mounting bracket (53.1) of the Hatch and simultaneously in the Ladder Connector. (Fig. B5.10)
6. Insert the tube linch pin (56.3) into the Ladder Connector (Fig. B5.11).  
→ Access Ladder is now mounted.




Fig. B5.06




Fig. B5.07




Fig. B5.08




Fig. B5.09




Fig. B5.10



Have all tube linch pins been mounted?

## Gap filling

Place timbers (9) between all Scaffold Decks MXK and MXH Heated Formwork.

1. Cut 12 x 4 cm timbers to a length of 2.38 m.
2. Cut out recess area (5.5 x 7 cm) 14.5 cm from the end of the timber for supporting the End Guardrail. (Fig. B5.14)
3. Position timber. (Fig. B5.12 + B5.13)
4. Nail timber to the Scaffold Bracket.  
→ Safety installations have now been mounted.




Fig. B5.12




Fig. B5.11




Fig. B5.13




Fig. B5.14

# B6 Additional Heated Panel Units

## Assembly

1. Erect second Heated Formwork Unit with the crane and connect by means of the Alignment Couplers BFD (30) and Compensation Walsers MAR (31). (Fig. B6.01)
2. Mount Base Plate (92), e.g. with PERI Anchor Bolt 14/20 x 130 (93).
3. Using PPE to prevent falling from a height, mount Side Mesh Barrier PMB and Stopend Guardrail MXK, see B5 Safety installations.
4. Release Combi Lifting Gear from the load-bearing point of the crane eye or lifting hook.
5. Erect additional Heated Formwork Units in the same way.




Fig. B6.01

## Closing formwork

- Erect the closing formwork in the same way. (Fig. B6.03)
- Progressively fix the Base Plates of the Push-Pull Props.
- Progressively install Tie Rods, see A4 Tie technology as well as Instructions for Assembly and Use for MAXIMO MX 15 / MX 18.
- PPE must be worn when assembling safety installations.




Fig. B6.03

## Tie Holder

for reliable storage of tie rods during the moving procedure. (Fig. B6.06)

### Assembly

1. Insert 4 hooks (34.1) of the tie holder (34) into the mounting slots (24) of the Heated Panel. (Fig. B6.04 + B6.05)
  - Adjustment bolt (34.2) is pressed down.
2. Push tie holder to the right.
  - Adjustment bolt engages and is secured.



The adjustment bolt (34.2) must be engaged in the mounting slot. If the spring force is missing, the tie holder must not be used!



**Danger of falling objects!**  
**Only tie rods may be accommodated!**




Fig. B6.04




Fig. B6.05




Fig. B6.06

# C1 Heating system – technical data

## Switch cabinet

### Power supply

3-phase alternating current 400 V /  
50 - 60 Hz  
Connected load max. 7200 W  
Maximum current consumption 12.5 A  
Protection Class 1  
IP 66

### Connection

CEE plug 400 V, 16 A, 6h

### Main switch

3-phase, mechanical separation +N (62)

### Control lamps

3 energy displays (64)  
1 fault indicator (63)  
(Fig. C.1.01)

### Safeguards

3 x 16 A, Tripping Characteristic B (69)

3-phase residual-current protection  
device 25 A (68)  
Conventional tripping current 30 mA  
4 auxiliary switches

### Control system

Omron Temperature Control E5BC (67)  
(Fig. C.1.02)

## Cables

Connecting cable 2.40 m yellow,  
7-pole (76)  
Connecting cable 1.20 m orange,  
5-pole (77)  
Non-interchangeable plug  
Protection Class 2  
IP 65  
Smallest bending radius 7.5 cm  
(Fig. C.1.03)




Fig. C.1.01




Fig. C.1.02




Fig. C.1.03

## Heating mat

Operating voltage 230V  
Current consumption 100 - 800 W  
(Fig. C.1.04)




Fig. C.1.04

### MXH Heated Formwork

Instructions for Assembly and Use – Standard Configuration

## Switch cabinet



- Carry out all work on electrical installations only when disconnected from the mains; disconnect all supply and connecting lines. Switch off the main switch.
- Secure main switch against unintentional re-start, e.g. by means of a padlock.
- Do not use damaged cables or components.

### Assembly

1. Insert 4 hooks (33.1) of the switch cabinet holder (33) into the mounting slots (24) of the Heated Panel.  
(Fig. C2.01 + C2.02)  
→ Adjustment bolt (33.2) is pressed down.
2. Push switch cabinet holder to the right.  
→ Adjustment bolt engages and is secured.



The adjustment bolt must be engaged in the mounting slot.  
If the spring force is missing, the switch cabinet must not be used!




Fig. C2.01




Fig. C2.02




Fig. C2.03




# C2 Heating system – assembly

## Cable connections



Firstly, connect the Heated Formwork Panels with each other, then with the switch cabinet.  
Then connect the supply line from the construction site distributor to the switch cabinet.




### Connections

Standard Heated Panels:

- 1 input socket (male) (79)
  - 2 output sockets (female) (80)
- (Fig. C2.04)

Extension Heated Panels:

- 1 input socket (male) (79)



### Cables


Connecting Cable MXH yellow, 2.40 m (76)

Connecting cable orange, 1.20 m (77)  
(Fig. C2.05)

Both cables are equipped with non-interchangeable couplings (male / female).  
When coupling, select the appropriate coupling side.

### Switch cabinet

- 61 Plug coupling 400 V, 16 A
- 62 Main switch
- 63 Fault indicator, red
- 64 Energy display, white
- 65 Switch cabinet lock
- 66 Type plate



## Establishing connections

Dry the sockets and plugs before coupling.  
Lock plug in place in the socket.

1. Connect the yellow connecting cable (76) from the output socket of the control cabinet (60) to the input socket (79) of the first Standard Heated Panel.
2. Using the orange connecting cables (77), connect the output sockets (80) of the Standard Heated Panel to the input sockets (79) of the Extension Heated Panel and the second Standard Heated Panel.
3. Correspondingly connect additional Extension Heated Panels and Standard Heated Panels. (Fig. C2.07)

Primary and closing formwork with a total length of max. 4.80 m can be connected via the stopend formwork. (Fig. C2.08)  
Protect connecting cable from protruding reinforcement steel.

## Connecting the site power supply

1. Switch off the switch cabinet main switch.
2. Then connect the cable with CEE plug 400 V, 16 A to the plug coupling (61) of the switch cabinet.
3. Protect supply cable with cable bridges.
4. Connect cable to the construction site main cabinet.




Fig. C2.07




Fig. C2.08



- Risk of burns! Heating wire and frame parts can become very hot! Do not touch during operations!
- Heating will remain hot for some time after being switched off! Allow to cool, wear protective gloves!




Fig. C3.01

## Switching on the heating system

1. Turn main switch on switch cabinet to the "ON" position.
2. Once a week, press test button (68.1) on the residual current circuit breaker. (Fig. C3.02) Residual current circuit breaker must be triggered. If the circuit breaker is not triggered, the switch cabinet is not to be operated.
3. Switch on the residual current circuit breaker (68.2) again.  
→ Heating system is operational

## Adjusting the temperature

After switching on, the control unit (67) displays the actual temperature value (70) and set value (71). The heating system becomes operational when the actual temperature value is lower than the set point. (Fig. C3.02a)  
The set point can be configured from +20°C to +80°C.

To increase the set point, press the "Up" (75) button.

To lower the set point, press the "Down" (76) button.

For additional settings of the control unit, see the manufacturer's data sheet in the appendix.

## Switching off the heating system

Turn main switch on switch cabinet to the "OFF" position.  
→ Heating system is now de-activated.




Fig. C3.02




Fig. C3.02a

## Troubleshooting

| Malfunction  | Cause   | Measures   |
|--|---|--|
| Control unit without function.                                 | <ul style="list-style-type: none"> <li>– No power supply from the construction site main cabinet.</li> <li>– Feed line is defective.</li> <li>– Main switch is switched off.</li> <li>– Residual current circuit breaker or fuses have tripped.</li> </ul>                  | <ul style="list-style-type: none"> <li>– Ensure power supply.</li> <li>– Change cable.</li> <li>– Switch on main switch.</li> <li>– Check heating system, switch on fuse or residual current circuit breaker again.</li> </ul>                                     |
| One Heated Panel does not function.                            | <ul style="list-style-type: none"> <li>– Connecting cable not properly connected or defective.</li> <li>– Defective heating mat.</li> </ul>   | <ul style="list-style-type: none"> <li>– Insert connection cable correctly and secure.</li> <li>– Replace the Heated Panel.</li> </ul>   |
| Control unit works, but no heating power on all Heated Panels. | <ul style="list-style-type: none"> <li>– Control unit incorrectly set.</li> <li>– Connecting cable to the first Heated Panel is not correctly connected or defective.</li> <li>– Orange connecting cable used from the switch cabinet to the first Heated Panel.</li> </ul> | <ul style="list-style-type: none"> <li>– Adjust the setting.</li> <li>– Connect the connecting cable to the correct sockets, replace the defective cable.</li> <li>– Use the yellow connecting cable from the switch cabinet to the first Heated Panel.</li> </ul> |
| Temperature is too low.  | <ul style="list-style-type: none"> <li>– Control unit is not set correctly.</li> <li>– Defective temperature sensor on the first Heated Panel.</li> <li>– Ambient temperature is too low.</li> </ul>  | <ul style="list-style-type: none"> <li>– Set control unit to a higher temperature.</li> <li>– Check the actual temperature value for plausibility, replace Heated Panel if necessary.</li> <li>– No remedial measure possible.</li> </ul>                          |
| Temperature is too high.                                       | <ul style="list-style-type: none"> <li>– Control unit is not set correctly.</li> <li>– Defective temperature sensor on the first Heated Panel.</li> </ul>   | <ul style="list-style-type: none"> <li>– Set control unit to a lower temperature.</li> <li>– Check the actual temperature value for plausibility, replace Heated Panel if necessary.</li> </ul>  |
| Fuses trip.  | <ul style="list-style-type: none"> <li>– Overload due to too many connected Heated Panels.</li> </ul>   | <ul style="list-style-type: none"> <li>– Uncouple excess Heated Panels, install an additional switch cabinet.</li> </ul>   |
| Residual current circuit breaker is triggered.                 | <ul style="list-style-type: none"> <li>– Moisture penetration causes earth fault.</li> <li>– Damaged wiring or heating wire causes earth fault.</li> </ul>  | <ul style="list-style-type: none"> <li>– Allow Heated Panels to dry.</li> <li>– Replace damaged cable or Heated Panel.</li> </ul>  |

# D1 Moving Heated Panel Units

## Maximum transport units

MXH Heated Formwork can be moved as Heated Formwork Units. When moving Heated Formwork Units with Extension MX 30, MXH 60 + MX 30 or MXH 120, a maximum of 2 units with a width of 2.40 m is permitted.

Permissible transportation units: see Fig. D1.01.

Attach crane lifting gear to the depicted load-bearing points.




Fig. D1.01

# D1 Moving Heated Panel Units

## Moving with the crane



- **Danger due to suspended load!**
- **Take into account the permissible load-bearing capacity of the crane lifting gear and the crane capacity!**
- **Follow Instructions for Use for Lifting Gear Combi MX and Lifting Hook MAXIMO 1.5 t!**



- **Heating will remain hot for some time after being switched off!**
- **Allow to cool, wear protective gloves!**



For working areas at great heights choose a safe working area, e.g. mobile scaffold.

### Heated Panel MXH

Move Heated Panel Unit, with or without Extension MXH, using the load-bearing point of the Crane Eye (10.2). (Fig. D1.02)




Fig. D1.02




Fig. D1.02a

### Panel MX 30

Use Lifting Hook MAXIMO 1.5 t for the Heated Panel Unit with Panel MX 30 as extension. (Fig. D1.02a)

### Assembly

1. Disconnect supply line from the construction site main cabinet (78) on the switch cabinet.
2. If necessary, uncouple connecting cable (76) on both sides of the lifting units. Close sockets with protective caps, insert couplings of the connecting cables against each other and place them in a secure position.
3. Remove Tie MX and store in tie holder.
4. Attach Combi Lifting Gear to the load-bearing point of the Crane Eye (10.2) or Lifting Hook (4).
5. Remove Alignment Couplers BFD (30) and Compensation Walers MAR 85 (31) from the lifting units. (Fig. D1.03)
6. Remove anchor bolts (93) from the Base Plates.
7. Move panel and clean, see E1 Cleaning.
8. Transport panel to next place of operation by crane.
9. Mount Base Plate (92), e.g. with PERI Anchor Bolt 14/20 x 130 (93).
10. Release Combi Lifting Gear from the load-bearing point of the Crane Eye or Lifting Hook.




Fig. D1.03

# D2 Dismantling Heated Panel Units



- **Danger due to suspended load!**
- **Take into account the permissible load-bearing capacity of the crane lifting gear and the crane capacity!**
- **Follow Instructions for Use for Lifting Gear Combi MX and Lifting Hook MAXIMO 1.5 t!**



For working areas at great heights choose a safe working area, e.g. mobile scaffold.

## Dismantling the units

1. Uncouple all supply and connecting cables on both sides. Close sockets with protective caps, insert couplings of the connecting cables against each other.
2. Dismantle the switch cabinet (33). Remove adjustment bolts (33.2) and push the switch cabinet to the left. (Fig. D2.02)
3. Remove the switch cabinet from the front. (Fig. D2.03)
4. Remove Tie MX from the Tie Holder.
5. Dismantle the Tie Holder in the same way as the switch cabinet.
6. Using PPE when dismantling the Side Mesh Barriers, Stopend Guardrails and Access Ladders on vertically-positioned units.
7. Attach Combi Lifting Gear to the load-bearing point of the Crane Eye or MAXIMO Lifting Hook.
8. Separate Heated Formwork Units from the vertical joint by removing Compensation Walers MAR and Alignment Couplers BFD, see D1 Moving Heated Formwork Units.
9. Release Base Plates of the Push-Pull Props on the Heated Formwork Unit which is to be moved.
10. Transport Heated Formwork Unit to designated area for dismantling.




Fig. D2.01




Fig. D2.02




Fig. D2.03

## Disassembling Heated Panel Units

1. Lay out timber (9) or planking as a base. The assembly area must be even.
2. Position Heated Panel Unit on support timbers using the crane.
3. Dismantle Guardrail Post MXK (52), Scaffold Deck MXK (51) and Scaffold Bracket MXK (50), see Instructions for Assembly and Use for the MAXIMO MXK Bracket System.
4. Dismantle Push-Pull Props (90), Kickers (91) and Base Plates (92).
5. Dismantle Connectors RS MXK (32).
6. Dismantle extensions by releasing the Alignment Couplers BFD.




Fig. D2.04

## Dismantling Heated Formwork Panels

1. Attach the Heated Formwork Panel MXH (10) with the Lifting Gear Combi MX (3) to the transport openings (10.9). (Fig. D2.05b)
2. Unscrew and remove 2 fixing bolts (37) each from all 4 corners. (Fig. D2.05a)
3. Lift Heated Panel MXH using the crane and move to the specified cleaning area. (Fig. D2.05)
4. Attach Panel MX in the same way and move to the specified cleaning area.




Fig. D2.05




Fig. D2.05a




Fig. D2.05b



## Cleaning

In order to maintain the value and operational readiness of the MXH Heated Formwork over a long period of time, the formwork should be carefully handled at all times.



- **Risk of slipping! Heated Panels are slippery to handle in wet or snowy conditions. Do not walk on Heated Panels!**
- **Never clean Heated Panels with a high pressure water jet.**
- **Do not use any oil or solvent-based cleaning agents.**

The electrical equipment of the Heating Panels is designed for non-pressurized water sprayed from all directions.

### Cleaning the rear side of the Heated Panel.

Whenever possible, immediately remove all fresh concrete with a cloth. Remove hardened concrete by means of a spatula.

Other forms of dirt are to be removed using water and a cloth.

### Cleaning of the heated side

Do not subject the heating wires to any mechanical stress. Only use a damp cloth for cleaning. Avoid direct exposure to water.

Clean frame parts with spatula, cloth and water.

Do not spray release agent on the frame parts but spread by means of a cloth. Ensure that the release agent does not come into contact with heating wires, cables, support fabric and insulating foam.




Fig. E1.01

## Maintenance



- **Carry out all work on electrical installations only when disconnected from the mains; disconnect all supply and connecting lines. Switch off the main switch.**
- **Secure main switch against switch-on, e.g. by means of a padlock.**
- **Do not use damaged cables or components.**
- **All work on electrical installations going beyond the described maintenance scope, must be carried out by a qualified electrician only.**

Ensure the cover sheets are securely fitted, fasten or change if necessary. Replace damaged insulation foam.

Check the heating pads for signs of damage and ensure they are securely fitted, fasten if necessary or have them changed by a qualified electrician.

Carry out a visual check of the heating wires and electrical connections for damaged insulation. If there are signs of damage, do not put Heated Panels into operation and have them changed by a qualified electrician.


Check sockets and connecting cables for signs of damage and proper insulation. Check sealing lips of the sockets for signs of damage and flexibility, if need be have them repaired by a qualified electrician.

## Periodic inspections

All electrical components of the MXH Heated Formwork have been inspected and furnished with an inspection plate according to DGUV (German Statutory Accident Insurance). The inspection plate indicates the month and date of the last inspection.

Once a year, an insulation test, protective conductor test, and a working current measurement of the whole MXH Heated Formwork is to be carried out by a qualified electrician.

In addition, all relevant national provisions must be complied with.



## Test Device MXH

The Test Device MXH is available for the function test.

It tests the electrical function of:

- Heated Panels,
- Extension Heated Panels,
- connector cables (yellow),
- connecting cables (orange).

Tests carried out:

- insulation,
- earthing,
- functionality of the heating mats,
- functionality of the temperature sensor.

For more information, refer to the Instructions for Use for the Test Device MXH.

## **Circuit diagrams**

|    |                  |    |
|----|------------------|----|
| F1 | Circuit diagrams | 44 |
| F2 | Switch cabinet   | 49 |
| F3 | Components list  | 52 |

## **Declaration of Conformity**


**56**

## **Data Sheet**

|                     |    |
|---------------------|----|
| OMRON E5CB          | 58 |
| Components          |    |
| MXH Heated Formwork | 66 |

# F1 Circuit diagrams


## Power supply



Power supply 3/N/PE 50Hz 400VAC  
CEE 16 A

# F1 Circuit diagrams


## Control system



# F1 Circuit diagrams




## Heated panel




# F1 Circuit diagrams

## Large extension panel




## Small extension panel




# F1 Circuit diagrams



## Connecting cable, yellow




## Connecting cable, orange







# F2 Switch cabinet

- Cabinet 1



- Cabinet 1



## Switch cabinet key


| Position number | Device designation | Type number           |
|-----------------|--------------------|-----------------------|
| 1               | H1                 | 3SUT001-6AAZ0-0AA0    |
| 2               | H2                 | 3SUT001-6AA60-0AA0    |
| 3               | H3                 | 3SUT001-6AA60-0AA0    |
| 4               | H4                 | 3SUT001-6AA60-0AA0    |
| 5               | S1                 | 3LD2103-1TL53         |
| 6               | X0                 | 26050                 |
| 7               | X1                 | HC-EVO-B06-BWSC-PLRBK |

# F2 Switch cabinet








## Switch cabinet key

| Position number | Device designation | Type number     |
|-----------------|--------------------|-----------------|
| 1               | F0                 | 5SV3342-6       |
| 2               | F0                 | 5ST3010         |
| 3               | F1                 | 5SL6116-6       |
| 4               | F1                 | 5ST3010         |
| 5               | F2                 | 5SL6116-6       |
| 6               | F2                 | 5ST3010         |
| 7               | F3                 | 5SL6116-6       |
| 8               | F3                 | 5ST3010         |
| 9               | K1                 | 3RF2320-IDA44   |
| 10              | K2                 | 3RF2320-IDA44   |
| 11              | K3                 | 3RF2320-IDA44   |
| 12              | PE                 | KM07E           |
| 13              | U1                 | E5GB01PAC100240 |



# F2 Switch cabinet


-E4 -E3 -E1/2 -X11



## Switch cabinet key

| Position number | Device designation | Type number       |
|-----------------|--------------------|-------------------|
| 1               | X10                | PT 2.5-QUATTRO    |
| 2               | X10                | PT 2.5-QUATTRO    |
| 3               | X10                | PT 2.5-QUATTRO    |
| 4               | X10                | PT 2.5-QUATTRO    |
| 5               | X10                | PT 2.5-QUATTRO    |
| 6               | X10                | PT 2.5-QUATTRO    |
| 7               | X10                | PT 2.5-QUATTRO-PE |
| 8               | X10                | PT 2.5-QUATTRO-PE |
| 9               | X10                | D-ST 2.5-QUATTRO  |
| 10              | X10                | CLIPFIX 3S        |
| 11              | X10                | CLIPFIX 3S        |

PE -E5 -X1 -X12



# F3 Components list



F01\_002\_LIT

## Components list

| Device designation<br>Position | Quantity<br>Signal<br>conversion<br>input | Designation   | Type number<br>Order number              | Manufacturer<br>Supplier | Item number<br>Function text | Pos |
|--------------------------------|---|---|--|--------------------------|------------------------------|-----|
| -Connection line               | 3<br>m                                    | PUR Control Cable PUR YELLOW JZ 7G1.5 mm² GE                          | PUR-GELB<br>22214                        | HELU<br>HELU             | HELU.22214                   |     |
| -F0                            | 1   | RCBO TYPE A 15/4 30MA 4TE<br>SENTRON residual current operated device | 5SV3342-6<br>5SV3342-6                   | SIE<br>SIE               | SIE.5SV3342-6                |     |
| -F0                            | 1<br>Qty                                  | Auxiliary switch 1make contact 1break contact<br>for circuit breaker  | 5ST3010<br>5ST3 010                      | SIE<br>SIE               | SIE.5ST3010                  |     |
| -F1                            | 1   | CIRCUIT BREAKER 230/400V 6KA, 1 POLE, B, 16A                          | 5SL6116-6<br>5SL6116-6                   | SIE<br>SIE               | SIE.5SL6116-6                |     |
| -F1                            | 1<br>Qty                                  | Auxiliary switch 1make contact 1break contact<br>for circuit breaker  | 5ST3010<br>5ST3 010                      | SIE<br>SIE               | SIE.5ST3010                  |     |
| -F2                            | 1   | CIRCUIT BREAKER 230/400V 6KA, 1 POLE, B, 16A                          | 5SL6116-6<br>5SL6116-6                   | SIE<br>SIE               | SIE.5SL6116-6                |     |
| -F2                            | 1<br>Qty                                  | Auxiliary switch 1make contact 1break contact<br>for circuit breaker  | 5ST3010<br>5ST3 010                      | SIE<br>SIE               | SIE.5ST3010                  |     |
| -F3                            | 1   | CIRCUIT BREAKER 230/400V 6KA, 1 POLE, B, 16A                          | 5SL6116-6<br>5SL6116-6                   | SIE<br>SIE               | SIE.5SL6116-6                |     |
| -F3                            | 1<br>Qty                                  | Auxiliary switch 1make contact 1break contact<br>for circuit breaker  | 5ST3010<br>5ST3 010                      | SIE<br>SIE               | SIE.5ST3010                  |     |
| -H1                            | 1   | SIGNAL LAMP, RED<br>SIRIUS ACT control and signalling devices         | 3SU1001-6AA20-0AA0<br>3SU1001-6AA20-0AA0 | SIE<br>SIE               | SIE.3SU1001-6AA20-0AA0       |     |
| -H1                            | 1   | LED MODULE, RED<br>SIRIUS ACT control and signalling devices          | 3SU1401-1BF20-3AA0<br>3SU1401-1BF20-3AA0 | SIE<br>SIE               | SIE.3SU1401-1BF20-3AA0       |     |
| -H1                            | 1   | HOLDER FOR 3 MODULES, PLASTIC   | 3SU1500-0AA10-0AA0<br>3SU1500-0AA10-0AA0 | SIE<br>SIE               | SIE.3SU1500-0AA10-0AA0       |     |
| -H2                            | 1   | SIGNAL LAMP, WHITE<br>SIRIUS ACT control and signalling devices       | 3SU1001-6AA60-0AA0<br>3SU1001-6AA60-0AA0 | SIE<br>SIE               | SIE.3SU1001-6AA60-0AA0       |     |
| -H2                            | 1   | LED MODULE, WHITE<br>SIRIUS ACT control and signalling devices        | 3SU1401-1BF60-3AA0<br>3SU1401-1BF60-3AA0 | SIE<br>SIE               | SIE.3SU1401-1BF60-3AA0       |     |
| -H2                            | 1   | HOLDER FOR 3 MODULES, PLASTIC   | 3SU1500-0AA10-0AA0<br>3SU1500-0AA10-0AA0 | SIE<br>SIE               | SIE.3SU1500-0AA10-0AA0       |     |
| -H3                            | 1   | SIGNAL LAMP, WHITE<br>SIRIUS ACT control and signalling devices       | 3SU1001-6AA60-0AA0<br>3SU1001-6AA60-0AA0 | SIE<br>SIE               | SIE.3SU1001-6AA60-0AA0       |     |
| -H3                            | 1   | LED MODULE, WHITE<br>SIRIUS ACT control and signalling devices        | 3SU1401-1BF60-3AA0<br>3SU1401-1BF60-3AA0 | SIE<br>SIE               | SIE.3SU1401-1BF60-3AA0       |     |
| -H3                            | 1   | HOLDER FOR 3 MODULES, PLASTIC   | 3SU1500-0AA10-0AA0<br>3SU1500-0AA10-0AA0 | SIE<br>SIE               | SIE.3SU1500-0AA10-0AA0       |     |

# F3 Components list



F01\_002\_LIT

## Components list

| Device designation<br>Position | Quantity<br>Signal<br>conversion<br>input | Designation   | Type number<br>Order number              | Manufacturer<br>Supplier | Item number<br>Function text | Pos |
|--------------------------------|---|---|--|--------------------------|------------------------------|-----|
| -H4                            | 1   | SIGNAL LAMP, WHITE<br>SIRIUS ACT control and signalling devices                                 | 3SU1001-6AA60-0AA0<br>3SU1001-6AA60-0AA0 | SIE<br>SIE               | SIE:3SU1001-6AA60-0AA0       |     |
| -H4                            | 1   | SIGNAL LAMP, WHITE<br>SIRIUS ACT control and signalling devices                                 | 3SU1401-1BF60-3AA0<br>3SU1401-1BF60-3AA0 | SIE<br>SIE               | SIE:3SU1401-1BF60-3AA0       |     |
| -H4                            | 1   | HOLDER FOR 3 MODULES, PLASTIC   | 3SU1500-0AA10-0AA0<br>3SU1500-0AA10-0AA0 | SIE<br>SIE               | SIE:3SU1500-0AA10-0AA0       |     |
| -K1                            | 1   | SEMI-CONDUCTOR 1-PHASE, 20A/48-460V, 4-30V DC<br>SCREW CONNECTION                               | 3RF2320-1DA44<br>3RF2320-1DA44           | SIE<br>SIE               | SIE:3RF2320-1DA44            |     |
| -K2                            | 1   | SEMI-CONDUCTOR 1-PHASE, 20A/48-460V, 4-30V DC<br>SCREW CONNECTION                               | 3RF2320-1DA44<br>3RF2320-1DA44           | SIE<br>SIE               | SIE:3RF2320-1DA44            |     |
| -K3                            | 1   | SEMI-CONDUCTOR 1-PHASE, 20A/48-460V, 4-30V DC<br>SCREW CONNECTION                               | 3RF2320-1DA44<br>3RF2320-1DA44           | SIE<br>SIE               | SIE:3RF2320-1DA44            |     |
| -PE                            | 1   | PE terminal block, 7 terminal points, for DIN mounting rail<br>Brass clamp                      | KM07E<br>KM07E                           | HGR<br>HAG               | HGR:KM07E                    |     |
| -S1                            | 1   | MAIN SWITCH 4-POLE Iu=25, 9.5KW RED-YELLOW  | 3LD2103-1TL53<br>3LD2103-1TL53           | SIE<br>SIE               | SIE:3LD2103-1TL53            |     |
| -S1                            | 1   | ADDITIONAL SIGN GERMAN/ENGLISH 47MM x 17MM<br>(ACCESSORIES FOR SWITCH 3LD2)                     | 3LD9286-1A<br>3LD9286-1A                 | SIE<br>SIE               | SIE:3LD9286-1A               |     |
| -Cabinet1                      | 1<br>Qty                                  | Compact switch cabinet B380 X H380 X T210 mm<br>painted, RAL 7035, one door with assembly plate | AE.1380500<br>1380.500                   | RIT<br>RIT               | RIT:1380500                  |     |
| -Cabinet1                      | 1<br>Qty                                  | Wall mounting bracket   | SZ.1590000<br>1590000                    | RIT<br>RIT               | RIT:1590000                  |     |
| -Cabinet1                      | 5<br>Qty                                  | End holder  | CLIPFIX 35<br>3022218                    | PXC<br>PXC               | PXC:3022218                  |     |
| -U1                            | 1   | Temperature Controller 100-240VAC<br>PT100  | E5CBQ1PAC100240<br>E5CB-Q1P AC100-240    | OMR<br>OMR               | OMR:E5CB-Q1PAC100-240        |     |
| -U1                            | 1   | DIN Rail Adapter<br>for E5CB-Q1P  | Y92F-52<br>Y92F-52                       | OMR<br>OMR               | OMR:Y92F-52                  |     |
| -Connecting cable              | 2<br>m                                    | PUR Control Cable PUR ORANGE JZ 5G1.5mm <sup>2</sup> OR   | PUR-ORANGE JZ/0Z<br>22018                | HELU<br>HELU             | HELU:22018                   |     |
| -WE1                           | 3<br>m                                    | Heat-resistant cable HELUTHERM® 145 MULTI 2x0.75 mm <sup>2</sup> SW                             | HELUTHERM® 145 MULTI<br>53412            | HELU<br>HELU             | HELU:53412                   |     |
| -WE3                           | 3<br>m                                    | Heat-resistant cable HELUTHERM® 145 MULTI 2x0.75 mm <sup>2</sup> SW                             | HELUTHERM® 145 MULTI<br>53412            | HELU<br>HELU             | HELU:53412                   |     |
| -WE4                           | 2<br>m                                    | Heat-resistant cable HELUTHERM® 145 MULTI 2x0.75 mm <sup>2</sup> SW                             | HELUTHERM® 145 MULTI<br>53412            | HELU<br>HELU             | HELU:53412                   |     |

### MXH Heated Formwork

Instructions for Assembly and Use – Standard Configuration

# F3 Components list



F01\_002\_LIT

## Components list

| Device designation<br>Position | Quantity<br>Signal<br>conversion<br>input | Designation   | Type number<br>Order number              | Manufacturer<br>Supplier | Item number<br>Function text | Pos |
|--------------------------------|---|---|--|--------------------------|------------------------------|-----|
| -WE5                           | 2<br>m                                    | Heat-resistant cable HELUTHERM® 145 MULTI 2x0.75 mm² SW     | HELUTHERM® 145 MULTI<br>53412            | HELU<br>HELU             | HELU.53412                   |     |
| -WX1                           | 3<br>m                                    | Heat-resistant cable HELUTHERM® 145 MULTI 7G1.5 mm² SW      | HELUTHERM® 145 MULTI<br>53457            | HELU<br>HELU             | HELU.53457                   |     |
| -WX11                          | 3<br>m                                    | Heat-resistant cable HELUTHERM® 145 MULTI 5G1.5 mm² SW      | HELUTHERM® 145 MULTI<br>53455            | HELU<br>HELU             | HELU.53455                   |     |
| -WX12                          | 3<br>m                                    | Heat-resistant cable HELUTHERM® 145 MULTI 3G1.5 mm² SW      | HELUTHERM® 145 MULTI<br>53453            | HELU<br>HELU             | HELU.53453                   |     |
| -WX20                          | 2<br>m                                    | Heat-resistant cable HELUTHERM® 145 MULTI 3G1.5 mm² SW      | HELUTHERM® 145 MULTI<br>53453            | HELU<br>HELU             | HELU.53453                   |     |
| -WX30                          | 2<br>m                                    | Heat-resistant cable HELUTHERM® 145 MULTI 3G1.5 mm² SW      | HELUTHERM® 145 MULTI<br>53453            | HELU<br>HELU             | HELU.53453                   |     |
| -X0                            | 1   | Appliance Inlet CEE 16A 5p 400V 6h IP44<br>for power supply | 26050<br>26050                           | BAS<br>HAG               | BAS.26050                    |     |
| -X1                            | 1<br>Qty                                  | Housing   | HC-EVO-B06-BWSC-PLRBK<br>1407622         | PXC<br>PXC               | PXC.1407622                  |     |
| -X1                            | 1<br>Qty                                  | Contact insert  | HC-B-06-IPT-F<br>1407727                 | PXC<br>PXC               | PXC.1407727                  |     |
| -X1                            | 1<br>Qty                                  | Housing   | HC-EVO-B06-HLFS-PLBK<br>1407619          | PXC<br>PXC               | PXC.1407619                  |     |
| -X1                            | 1<br>Qty                                  | Cable screw connection                                      | HC-B-G-M20-PLRBK<br>1407669              | PXC<br>PXC               | PXC.1407669                  |     |
| -X1                            | 1<br>Qty                                  | Contact insert  | HC-B-06-IPT-M<br>1407728                 | PXC<br>PXC               | PXC.1407728                  |     |
| -X1.                           | 1<br>Qty                                  | Housing   | HC-EVO-B06-SHWSC-2SSM32-PLRBK<br>1407624 | PXC<br>PXC               | PXC.1407624                  |     |
| -X1.                           | 1<br>Qty                                  | Contact insert  | HC-B-06-IPT-M<br>1407728                 | PXC<br>PXC               | PXC.1407728                  |     |
| -X1.                           | 1<br>Qty                                  | Housing   | HC-EVO-B06-HLFS-PLBK<br>1407619          | PXC<br>PXC               | PXC.1407619                  |     |
| -X1.                           | 1<br>Qty                                  | Cable screw connection                                      | HC-B-G-M20-PLRBK<br>1407669              | PXC<br>PXC               | PXC.1407669                  |     |
| -X1.                           | 1<br>Qty                                  | Contact insert  | HC-B-06-IPT-F<br>1407727                 | PXC<br>PXC               | PXC.1407727                  |     |
| -X11                           | 1<br>Qty                                  | Housing   | HC-EVO-B06-SHWSC-2SSM32-PLRBK<br>1407624 | PXC<br>PXC               | PXC.1407624                  |     |

# F3 Components list

F01\_002\_LIT

## Components list

| Device designation<br>Position | Quantity<br>Signal<br>conversion<br>input | Designation   | Type number<br>Order number              | Manufacturer<br>Supplier | Item number<br>Function text | Pos |
|--------------------------------|---|---|--|--------------------------|------------------------------|-----|
| -X11                           | 1<br>Qty                                  | Contact insert  | HC-B 06-I-PTFF<br>1407727                | PXC<br>PXC               | PXC.1407727                  |     |
| -X11                           | 1<br>Qty                                  | Housing   | HC-EVO-B06-HLFS-PLBK<br>1407619          | PXC<br>PXC               | PXC.1407619                  |     |
| -X11                           | 1<br>Qty                                  | Cable screw connection  | HC-B-G-M20-PLRBK<br>1407669              | PXC<br>PXC               | PXC.1407669                  |     |
| -X11                           | 1<br>Qty                                  | Contact insert  | HC-B 06-I-PTM<br>1407728                 | PXC<br>PXC               | PXC.1407728                  |     |
| -X11                           | 1<br>Qty                                  | Housing   | HC-EVO-B06-HLFS-PLBK<br>1407619          | PXC<br>PXC               | PXC.1407619                  |     |
| -X11                           | 1<br>Qty                                  | Cable screw connection  | HC-B-G-M20-PLRBK<br>1407669              | PXC<br>PXC               | PXC.1407669                  |     |
| -X11                           | 1<br>Qty                                  | Contact insert  | HC-B 06-I-PTFF<br>1407727                | PXC<br>PXC               | PXC.1407727                  |     |
| -X12                           | 1<br>Qty                                  | Housing   | HC-EVO-B06-SHWSC-2SSM32-PLRBK<br>1407624 | PXC<br>PXC               | PXC.1407624                  |     |
| -X12                           | 1<br>Qty                                  | Contact insert  | HC-B 06-I-PTFF<br>1407727                | PXC<br>PXC               | PXC.1407727                  |     |
| -X20                           | 1<br>Qty                                  | Housing   | HC-EVO-B06-SHWSC-2SSM32-PLRBK<br>1407624 | PXC<br>PXC               | PXC.1407624                  |     |
| -X20                           | 1<br>Qty                                  | Contact insert  | HC-B 06-I-PTM<br>1407728                 | PXC<br>PXC               | PXC.1407728                  |     |
| -X30                           | 1<br>Qty                                  | Housing   | HC-EVO-B06-SHWSC-2SSM32-PLRBK<br>1407624 | PXC<br>PXC               | PXC.1407624                  |     |
| -X30                           | 1<br>Qty                                  | Contact insert  | HC-B 06-I-PTM<br>1407728                 | PXC<br>PXC               | PXC.1407728                  |     |
| +KK                            | 1<br>Qty                                  | Terminal boxes KL without flange, WHD 150x150x80 mm painted, without flange plate and mounting plate RAL 7035 | KL.1514510<br>1514510                    | RIT<br>RIT               | RIT.1514510                  |     |
| +KKX10                         | 14<br>Qty                                 | Feed-through terminal   | PT 2,5-QUATTRO<br>3209578                | PXC<br>PXC               | PHO.3209578                  |     |
| +KKX10                         | 4<br>Qty                                  | PE terminal   | PIT 2,5-QUATTRO-PE<br>3209594            | PHO<br>PHO               | PHO.3209594                  |     |
| +KKX10                         | 2<br>Qty                                  | Connection cover  | D-ST 2,5-QUATTRO<br>3030514              | PHO<br>PHO               | PHO.3030514                  |     |
| +KKX10                         | 2<br>Qty                                  | End holder  | CLIPFIX 35<br>3022218                    | PXC<br>PXC               | PXC.3022218                  |     |

## Part F EC Declaration of Conformity

### EG- Konformitätserklärung

im Sinne der EG-Richtlinie 2004/108/EG  
Anhang IV, 2.

**In der Gemeinschaft ansässige Person, die bevollmächtigt ist, die technischen Unterlagen zusammenzustellen:**

PERI GmbH  
Rudolf-Diesel-Strasse 19  
89259 Weißenhorn

#### Beschreibung und Identifizierung des Produktes:

|                     |  |
|---------------------|--|
| Produktgruppe:      | Wandschalung   |
| Typ:                | Heizbare Schalung  |
| Artikel-Nr.:        | 129132 129135 129330<br>129133 129370 128874<br>129134 129375 128875 |
| Handelsbezeichnung: | MXH Heizbare Schalung  |

**Es wird ausdrücklich erklärt, dass das Produkt allen einschlägigen Bestimmungen der folgenden EG-Richtlinien entspricht:**

EMV 2004/108/EG  
Die Schutzziele der NSP-RL 2006/95/EG sind eingehalten.

**Fundstelle der angewandten harmonisierten Normen entsprechend Artikel 6 Absatz 2:**

EN 12100 : 2011:3  
EN 13849 - 1 : 2008 -12  
EN 60204 - 1 : 2006:6  
EN 62395 - 1 : 2006:9

Weißenhorn, 05.10.2015

**Hersteller**  
PERI GmbH  
Postfach 1264  
89259 Weißenhorn

**Leitung Produktentwicklung**

Dipl.-Ing. Rainer Bolz  
PERI GmbH



## Part F EC Declaration of Conformity

This document is a translation into English from the German original.

### EC Declaration of Conformity

as defined in EC Directive 2004/108/EC  
Appendix IV, 2.

**Person residing within the Community authorised to compile the relevant technical documentation:**

PERI GmbH  
Rudolf-Diesel-Strasse 19  
89259 Weissenhorn / Germany

**Description and identification of the product:**

|                |  |
|----------------|--|
| Product group: | Wall Formwork  |
| Type:          | Heated Formwork  |
| Item no.:      | 129132 129135 129330<br>129133 129370 128874<br>129134 129375 128875 |
| Trade name:    | MXH Heated Formwork  |

**This explicitly states that the product fulfils all relevant provisions of the following EC Directives:**

EMC 2004/108/EC  
The safety objectives of NSP-RL 2006/95/EC have been complied with.

**Reference to the harmonised standards used, as referred to in Article 6 paragraph 2:**

EN 12100 : 2011:3  
EN 13849 - 1 : 2008 -12  
EN 60204 - 1 : 2006:6  
EN 62395 - 1 : 2006:9

Weissenhorn, 05.10.2015

**Manufacturer**  
PERI GmbH  
P.O. Box 1264  
89259 Weissenhorn / Germany

-----  
**Head of Product Development**  
Dipl. -Ing. Rainer Bolz  
PERI GmbH

## Temperature Controller E5CB (48 × 48 mm)

**Ideal for heater control, these Temperature Controllers offer the highest control performance at surprisingly low cost!**

**Easy to Read with One of the Largest Character Displays Anywhere.**

- Improved visibility with character height of approx. 16 mm.
- Depth beyond front panel: Only 60 mm.
- Fewer parameters for simple setup.
- Faster sampling at 250 ms.
- High reliability with a three-year warranty.




48 × 48 mm

**NEW**

Refer to *Safety Precautions* on page 8.

### Main I/O Functions



### Model Number Structure

#### Model Number Legend

E5CB-□1□□  
1 2 3 4

- Control Output**  
R: Relay output: 250 VAC, 3 A  
Q: Voltage output (for driving SSR): 12 VDC, 21 mA
- Alarm**  
1: Relay output: 250 VAC, 1 A (resistive load)
- Sensor type**  
TC: Thermocouple (K, J, T, R, or S)  
P: Platinum resistance thermometer (Pt100)
- Power Supply Voltage**  
Blank: 100 to 240 VAC  
D: 24 VAC/VDC

OMRON

1

## E5CB

### Ordering Information

#### Temperature Controllers

| Size               | Power supply voltage            | Input type                      | Alarm output | Control output                      | Model        |            |
|--------------------|---------------------------------|---------------------------------|--------------|-------------------------------------|--------------|------------|
| E5CB<br>48 × 48 mm | 100 to 240 VAC                  | Thermocouple                    | 1            | Relay output                        | E5CB-R1TC    |            |
|                    |                                 | Platinum resistance thermometer |              |                                     | E5CB-R1P     |            |
|                    |                                 | Thermocouple                    |              | Voltage output<br>(for driving SSR) | E5CB-Q1TC    |            |
|                    |                                 | Platinum resistance thermometer |              |                                     | E5CB-Q1P     |            |
|                    |                                 | 24 VAC/VDC                      |              | Thermocouple                        | Relay output | E5CB-R1TCD |
|                    |                                 |                                 |              | Platinum resistance thermometer     | E5CB-R1PD    |            |
|                    | Thermocouple                    |                                 |              | Voltage output<br>(for driving SSR) | E5CB-Q1TCD   |            |
|                    | Platinum resistance thermometer |                                 |              |                                     | E5CB-Q1PD    |            |

#### Accessories (Order Separately)

##### Terminal Cover

|       |           |
|-------|-----------|
| Model | E53-COV19 |
|-------|-----------|

##### Front Cover

| Type             | Model    |
|------------------|----------|
| Hard Front Cover | Y92A-48B |
| Soft Front Cover | Y92A-48D |

##### USB-Serial Conversion Cable

|       |           |
|-------|-----------|
| Model | E58-CIFQ2 |
|-------|-----------|

##### Mounting Adapter (Included)

|       |         |
|-------|---------|
| Model | Y92F-49 |
|-------|---------|

##### Adapter

|       |         |
|-------|---------|
| Model | Y92F-45 |
|-------|---------|

- Note: 1. Use this Adapter when the Front Panel has already been prepared for the E5B□.  
2. Only black is available.

##### Waterproof Packing (Included)

|       |         |
|-------|---------|
| Model | Y92S-P6 |
|-------|---------|

##### Unit Seal

|       |         |
|-------|---------|
| Model | Y92S-L2 |
|-------|---------|

## Specifications

### Ratings

|                               |   |
|-------------------------------|---|
| Power supply voltage          | 100 to 240 VAC 50/60 Hz, 24 VAC 50/60 Hz, or 24 VDC   |
| Operating voltage range       | 85% to 110% of rated supply voltage   |
| Power consumption             | Approx. 3.5 VA (100 to 240 VAC)<br>Approx. 3.5 VA (24 VAC)<br>Approx. 2.5 W (24 VDC)  |
| Sensor input                  | Models with thermocouple inputs<br>Thermocouple: K, J, T, R, or S (JIS C 1602-1995, IEC60584-1)<br>Models with platinum resistance thermometer inputs<br>Platinum resistance thermometer: Pt100 (JIS C 1604-1997, IEC60751) |
| Control output                | Relay output  |
|                               | Voltage output<br>(for driving SSR)   |
| Alarm output                  | SPST-NO, 250 VAC, 3 A (resistive load), electrical life: 100,000 operations, minimum applicable load: 5 V, 10 mA  |
| Control method                | ON/OFF control or 2-PID control (with auto-tuning)  |
| Setting method                | Digital setting using front panel keys  |
| Indication method             | 7-segment digital display and individual indicators<br>Character height: 16.2 mm (PV)   |
| Other functions               | Temperature input shift, run/stop, protection functions, etc.   |
| Ambient operating temperature | -10 to 55°C (with no condensation or icing)/With a three-year guarantee: -10 to 50°C  |
| Ambient operating humidity    | 25% to 85%  |
| Storage temperature           | -25 to 65°C (with no condensation or icing)   |

## E5CB

### Input Ranges

#### Models with Thermocouple Inputs

| Model<br>(temperature input) | Set value | Input type | Range           |                 |
|------------------------------|-----------|------------|-----------------|-----------------|
|                              |           |            | °C              | °F              |
| TC input                     | 0         | K          | -200 to 1,300   | -300 to 2,300   |
|                              | 1         |            | -20.0 to 500.0  | 0.0 to 900.0    |
|                              | 2         | J          | -100 to 850     | -100 to 1500    |
|                              | 3         |            | -20.0 to 400.0  | 0.0 to 750.0    |
|                              | 4         | T          | -200 to 400     | -300 to 700     |
|                              | 5         |            | -199.9 to 400.0 | -199.9 to 700.0 |
|                              | 6         |            | R               | 0 to 1,700      |
| 7                            | S         | 0 to 1,700 | 0 to 3,000      |                 |

Default setting: 0

Applicable standards (K, J, T, R, S): JIS C1602-1995 and IEC 60584-1

#### Platinum Resistance Thermometer Input

| Model<br>(temperature input) | Set value | Input type | Range           |                 |
|------------------------------|-----------|------------|-----------------|-----------------|
|                              |           |            | °C              | °F              |
| Pt input                     | 8         | Pt100      | -200 to 850     | -300 to 1500    |
|                              | 9         |            | -199.9 to 500.0 | -199.9 to 900.0 |

Default setting: 8

Applicable standards (Pt100): JIS C1604-1997 and IEC 60751

### Alarm Types

Select alarm types out of the 11 alarm types listed in the following table.

| Setting             | Alarm type                                     | Positive alarm value (X) | Negative alarm value (X) | Deviation alarm/absolute value alarm |
|---------------------|--|--------------------------|--------------------------|--------------------------------------|
| 0                   | No alarm                                       | Output OFF               |                          |                                      |
| 1                   | Upper/lower limit                              |                          | Always ON                | Deviation alarm                      |
| 2                   | Upper limit                                    |                          |                          | Deviation alarm                      |
| 3                   | Lower limit                                    |                          |                          | Deviation alarm                      |
| 4                   | Upper/lower range                              |                          | Always OFF               | Deviation alarm                      |
| 5<br>(See note 2.)  | Upper/lower limit standby sequence ON          |                          | Always OFF               | Deviation alarm                      |
| 6<br>(See note 2.)  | Upper limit standby sequence ON                |                          |                          | Deviation alarm                      |
| 7<br>(See note 2.)  | Lower limit standby sequence ON                |                          |                          | Deviation alarm                      |
| 8                   | Absolute value upper limit                     |                          |                          | Absolute value alarm                 |
| 9                   | Absolute value lower limit                     |                          |                          | Absolute value alarm                 |
| 10<br>(See note 2.) | Absolute value upper limit standby sequence ON |                          |                          | Absolute value alarm                 |
| 11<br>(See note 2.) | Absolute value lower limit standby sequence ON |                          |                          | Absolute value alarm                 |
| 12                  | Do not set.                                    |                          |                          |                                      |

**Note:** 1. The default is 2.

2. Alarms with a Standby Sequence

The alarm is blocked until the first safe-state is reached.


Unwanted alarm during start-up are prevented.

Example: Deviation Lower Limit Standby Sequence ON

The standby sequence is cleared when the alarm OFF condition has been met.

The standby sequence is started again when any of the following conditions is met.

- Operation is started (power is turned ON or operation is switched from stop to run).
- The alarm value is changed.
- The temperature input offset is changed.
- The set point is changed.




## E5CB

### Characteristics

|   |  |  |
|---|--|--|
| <b>Indication accuracy</b>                    | Thermocouple: (See note 1.)<br>(±0.5% of indicated value or ±1°C, whichever is greater) ±1 digit max.<br>Platinum resistance thermometer:<br>(±0.5% of indicated value or ±1°C, whichever is greater) ±1 digit max.  |  |
| <b>Influence of temperature (See note 2.)</b> | R and S thermocouple inputs: (±1% of PV or ±10°C, whichever is greater) ±1 digit max.  |  |
| <b>Influence of voltage (See note 2.)</b>     | K, J, and T thermocouple inputs: (±1% of PV or ±4°C, whichever is greater) ±1 digit max.<br>Platinum resistance thermometer inputs: (±1% of PV or ±2°C, whichever is greater) ±1 digit max.  |  |
| <b>Hysteresis</b>                             | 0.1 to 999.9 (in units of 0.1) °C/°F   |  |
| <b>Proportional band (P)</b>                  | 0.1 to 999.9 (in units of 0.1) °C/°F   |  |
| <b>Integral time (I)</b>                      | 0 to 3999 s (in units of 1 s)  |  |
| <b>Derivative time (D)</b>                    | 0 to 3999 s (in units of 1 s)  |  |
| <b>Control period</b>                         | 0.5, 1 to 99 s (in units of 1 s)   |  |
| <b>Alarm setting range</b>                    | -1999 to 9999 (decimal point position depends on input type)   |  |
| <b>Input sampling period</b>                  | 250 ms   |  |
| <b>Affect of signal source resistance</b>     | Thermocouple: 0.1°C/Ω max. (100 Ω max.) (See note 3.)<br>Platinum resistance thermometer: 0.6°C/Ω max. (10 Ω max.)   |  |
| <b>Insulation resistance</b>                  | 20 MΩ min. (at 500 VDC)  |  |
| <b>Dielectric strength</b>                    | 2,300 VAC, 50 or 60 Hz for 1 min (between terminals with different charge)   |  |
| <b>Vibration resistance</b>                   | <b>Malfunction</b>   | 10 to 55 Hz, 20 m/s <sup>2</sup> for 10 min each in X, Y, and Z directions                                   |
|   | <b>Destruction</b>   | 10 to 55 Hz, 20 m/s <sup>2</sup> for 2 hrs each in X, Y, and Z directions                                    |
| <b>Shock resistance</b>                       | <b>Malfunction</b>   | 200 m/s <sup>2</sup> , 3 times each in X, Y, and Z directions  |
|   | <b>Destruction</b>   | 300 m/s <sup>2</sup> , 3 times each in X, Y, and Z directions  |
| <b>Weight</b>                                 | Controller: Approx. 100 g, Mounting Bracket: Approx. 10 g  |  |
| <b>Degree of protection</b>                   | Front panel: IP66<br>Rear case: IP20, Terminals: IP00  |  |
| <b>Memory protection</b>                      | Non-volatile memory (number of writes: 100,000 times)  |  |
| <b>Conformed standards</b>                    | <b>Certified standards</b>   | UL 61010-1, CSA C22.2 No. 1010-1   |
|   | <b>Applicable standards</b>  | EN61326, EN61010-1, IEC61010-1<br>VDE0106, Part 100 (Finger protection), when the terminal cover is mounted. |
| <b>EMC</b>                                    | EMI<br>Emission Enclosure: EN61326<br>Emission AC Mains: EN50111 Group1 Class A<br>EMS<br>Immunity ESD: EN61326<br>Immunity RF-interference: EN61000-4-2<br>Immunity Burst: EN61000-4-3<br>Conduction Disturbance Immunity: EN61000-4-4<br>Immunity Surge: EN61000-4-6<br>Immunity Voltage Dip/Interrupting: EN61000-4-5<br>EN61000-4-11 |  |

- Note:** 1. The indication accuracy of K and T thermocouples at a temperature of -100°C max. is ±2°C ±1 digit maximum. The indication accuracy of the R and S thermocouples at a temperature of 200°C max. is ±3°C ±1 digit max.  
2. Conditions: Ambient temperature: -10 to 23 to 55°C, Voltage range: -15% to ±10% of rated voltage  
3. R, and S sensors: 0.2°C/Ω max. (100 Ω max.)

### Electrical Life Expectancy Curve for Relays (Reference Values)



### USB-Serial Conversion Cable Specifications

|                                 |  |
|---------------------------------|--|
| <b>Applicable OS</b>            | Windows 2000, XP, Vista, or 7  |
| <b>Applicable software</b>      | Thermo Mini  |
| <b>Applicable models</b>        | E5CB Series  |
| <b>USB interface standard</b>   | USB specification 1.1  |
| <b>DTE speed</b>                | 38,400 bps   |
| <b>Connector Specifications</b> | Computer: USB (Type A plug)<br>Temperature Controller: Special serial connector        |
| <b>Power supply</b>             | Bus power (supplied from the USB host controller)                                      |
| <b>Power supply voltage</b>     | 5 VDC  |
| <b>Current consumption</b>      | 450 mA max.  |
| <b>Output voltage</b>           | 4.7±0.2 VDC (Supplied from USB-Serial Conversion Cable to the Temperature Controller.) |
| <b>Output current</b>           | 250 mA max. (Supplied from USB-Serial Conversion Cable to the Temperature Controller.) |
| <b>Ambient temperature</b>      | 0 to 55°C (with no condensation or icing)  |
| <b>Ambient humidity</b>         | 10% to 80%   |
| <b>Storage temperature</b>      | -20 to 60°C (with no condensation or icing)  |
| <b>Storage humidity</b>         | 10% to 80%   |
| <b>Altitude</b>                 | 2,000 m max.   |
| <b>Weight</b>                   | Approx. 120 g  |


- Note:** 1. A high-power port is used for the USB port.  
2. A driver must be installed on the computer. Refer to the *Instruction Manual* included with the Cable for the installation procedure.

## E5CB

### External Connections


- A voltage output (control output) is not electrically insulated from the internal circuits. When using a grounding thermocouple, do not connect any of the control output terminals to ground. If the control output terminals are connected to ground, errors will occur in the measured temperature values as a result of leakage current.

#### E5CB



### Nomenclature

#### E5CB




- |                   |  |  |
|-------------------|--|--|
| (1) Display No. 1 | Displays the process value (PV) or parameter.                                | (10)  Press these keys for at least 3 seconds in Operation Level or Adjustment Level to go to Protect Level. Press these keys for at least 1 second in Protect Level to return to Operation Level. |
| (2) Display No. 2 | Displays the set point (SP) or parameter setting.                            |  |
| (3) ALM           | Lit while the alarm is ON. Not lit while the alarm is OFF.                   | (11)  Press these keys for at least 2 seconds to start or stop autotuning.*1   |
| (4) OUT           | Lit while the control output is ON. Not lit while the control output is OFF. | (12)  Press these keys for at least 2 seconds to start or stop operation.*2  |
| (5) STOP          | Not lit during operation. Lit while operation is stopped.                    |  |
| (6)               | Level Key: Changes the setting level.  | *1: These keys are disabled when starting and stopping autotuning has been disabled with operation control key protection.   |
| (7)               | Mode Key: Changes the parameter within the setting level.                    | *2: These keys are disabled when starting and stopping operation has been disabled with operation control key protection.  |
| (8)               | Down Key: Reduces the setting.   |  |
| (9)               | Up Key: Increases the setting.   |  |

### Dimensions

(Unit: mm)

#### E5CB




The Support Software port is on the top of the Temperature Controller. This port is used to connect the Temperature Controller to a personal computer. The E58-CIFQ2 USB-Serial Conversion Cable is required to make the connection. For details on connection methods, refer to the *E58-CIFQ2 USB-Serial Conversion Cable Instruction Manual*. \*Do not leave the USB-Serial Conversion Cable connected while using the Temperature Controller.

## E5CB


### Accessories (Order Separately)

#### Terminal Cover E53-COV19




Note: The E53-COV10 cannot be used.

#### Waterproof Packing Y92S-P6




Order the Waterproof Packing separately if it becomes lost or damaged. The Waterproof Packing can be used to achieve an IP66 degree of protection. (Deterioration, shrinking, or hardening of the waterproof packing may occur depending on the operating environment. Therefore, periodic replacement is recommended to ensure the level of waterproofing specified in IP66. The time for periodic replacement depends on the operating environment. Be sure to confirm this point at your site. Consider one year a rough standard. OMRON shall not be liable for the level of water resistance if the customer does not perform periodic replacement.) The Waterproof Packing does not need to be attached if a waterproof structure is not required.

#### Unit Labels Y92S-C2



The Unit Labels for the Digital Panel Meter are used. Use either the °C or °F label from the sheet.




#### USB-Serial Conversion Cable E58-CIFQ2






#### Adapter

- Note: 1. Use this Adapter when the Front Panel has already been prepared for the E5B□.
2. Only black is available.
3. You cannot use the E58-CIFQ2 USB-Serial Conversion Cable if you use the Y92F-45 Adapter. To use the USB-Serial Conversion Cable to make the settings, do so before you mount the Temperature Controller in the panel.

#### Y92F-45



#### Mounted to E5CB



#### Front Covers

- Front Covers are available. Use them in the following cases.
- To protect the setting panel from dust and dirt
  - To prevent inadvertently touching the setting panel and accidentally changing the settings
  - To help protect the front panel from water drops
  - To help protect the Temperature Controller from static electricity



- Note: 1. The Y92A-48B Front Cover is made from hard plastic. It must be removed to change the settings. The Y92A-48D Front Cover is made from PVC. You can press the front of the Front Cover to change the settings. However, the Front Cover makes it more difficult to change the settings. Confirm applicability in advance.
2. The Soft Front Cover may deteriorate, shrink, or harden due to the application environment. We recommend replacing it periodically.

## E5CB


### Operating Procedure

#### Parameters

Depending on the settings, some data may not be displayed.

For details, refer to the *Instruction Manual*.

Operation will stop when the level is switched from Operation Level to Initial Setting Level.



### Troubleshooting

When an error has occurred, the display No. 1 shows the error code.

Take necessary measure according to the error code, referring the following table.

| Display                    | Meaning                   | Action  |
|----------------------------|---------------------------|---|
| SERR<br>(S.ERR)            | Input error:*1            | Check the wiring of inputs, disconnections, short circuits and input type.  |
| E111<br>(E111)             | RAM memory error          | Turn the power OFF then back ON again.*2  |
| E111/SUM<br>(E111)/(SUM)*3 | Non-volatile memory error | Press the  and  Keys for at least 3 seconds to initialize the settings and clear the non-volatile memory error.*2 |

• The control output and the alarm output will turn OFF when an error occurs. (For SERR, the alarm output will be processed for a high temperature error.)

• If the input value exceeds the display limit (–1999 to 9999) but it is still within the control range, cccc will be displayed for values under –1999. Under these conditions, the control output and alarm output will operate normally.

\*1. This error is displayed only when the process value and set point are displayed.

\*2. If the display does not change, the Controller needs to be repaired.

If operation returns to normal, then noise may have caused the problem. Check for noise.

\*3. E111 will be displayed on display No. 1 and SUM will be displayed on display No. 2.



## E5CB

### Safety Precautions

Refer to *Safety Precautions for All Temperature Controllers*.

#### CAUTION

|  |  |
|--|--|
| Do not touch the terminals while power is being supplied. Doing so may occasionally result in minor injury due to electric shock.  |  |
| Do not allow pieces of metal, wire clippings, or fine metallic shavings or filings from installation to enter the product. Doing so may occasionally result in electric shock, fire, or malfunction.   |  |
| Do not use the product where subject to flammable or explosive gas. Otherwise, minor injury from explosion may occasionally occur.   |  |
| Do not use the Temperature Controller or the USB-Serial Conversion Cable if it is damaged. Doing so may occasionally result in minor electric shock or fire.   |  |
| Never disassemble, modify, or repair the product or touch any of the internal parts. Minor electric shock, fire, or malfunction may occasionally occur.  |  |
| <b>CAUTION - Risk of Fire and Electric Shock</b><br>a) More than one disconnect switch may be required to de-energize the equipment before servicing the product.<br>b) Caution: To reduce the risk of fire or electric shock, do not interconnect the outputs of different Class 2 circuits. *  |  |
| If the output relays are used past their life expectancy, contact fusing or burning may occasionally occur. Always consider the application conditions and use the output relays within their rated load and electrical life expectancy. The life expectancy of output relays varies considerably with the output load and switching conditions. |  |
| Tighten the terminal screws to the rated torque of between 0.74 and 0.90 N·m. Loose screws may occasionally result in fire.  |  |
| Set the parameters of the product so that they are suitable for the system being controlled. If they are not suitable, unexpected operation may occasionally result in property damage or accidents.   |  |
| A malfunction in the product may occasionally make control operations impossible or prevent alarm outputs, resulting in property damage. To maintain safety in the event of malfunction of the product, take appropriate safety measures, such as installing a monitoring device on a separate line.   |  |
| Do not allow pieces of metal or wire cuttings to get inside the USB-Serial Conversion Cable connector for the Support Software. Failure to do so may occasionally result in minor electric shock, fire, or damage to equipment.  |  |
| Do not allow dust and dirt to collect between the pins in the connector on the USB-Serial Conversion Cable. Failure to do so may occasionally result in fire.  |  |

\* A class 2 power supply is one tested and certified by UL as having the current and voltage of the secondary output restricted to specific levels.

### Precautions for Safe Use

Be sure to observe the following precautions to prevent malfunction or adverse effects on the performance or functionality of the product. Not doing so may occasionally result in faulty operation.

- This product is specifically designed for indoor use only. Do not use this product in the following places:
  - Places directly subject to heat radiated from heating equipment.
  - Places subject to splashing liquid or oil atmosphere.
  - Places subject to direct sunlight.
  - Places subject to dust or corrosive gas (in particular, sulfide gas and ammonia gas).
  - Places subject to intense temperature change.
  - Places subject to icing and condensation.
  - Places subject to vibration and large shocks.
- Use and store the product within the rated ambient temperature and humidity. Gang-mounting two or more Temperature Controllers, or mounting Temperature Controllers above each other may cause heat to build up inside the Temperature Controllers, which will shorten their service life. In such a case, use forced cooling by fans or other means of air ventilation to cool down the Temperature Controllers.
- To allow heat to escape, do not block the area around the product. Do not block the ventilation holes on the product.
- Be sure to wire properly with correct polarity of terminals.
- Use the specified size of crimp terminals for wiring (M3.5, width of 7.2 mm or less). For open-wired connections use stranded or solid copper wires with a gauge of AWG24 to AWG14 (equal to a cross-sectional area of 0.205 to 2.081 mm<sup>2</sup>). (The stripping length is 5 to 6 mm.) Up to two wires of the same size and type or two crimp terminals can be connected to one terminal. Do not connect more than two wires or more than two crimp terminals to the same terminal.
- Do not wire the terminals that are not used.
- To avoid inductive noise, keep the wiring for the product's terminal block away from power cables carry high voltages or large currents. Also, do not wire power lines together with or parallel to product wiring. Using shielded cables and using separate conduits or ducts is recommended. Attach a surge suppressor or noise filter to peripheral devices that generate noise (in particular, motors, transformers, solenoids, magnetic coils, or other equipment that have an inductance component). When a noise filter is used at the power supply, first check the voltage or current, and attach the noise filter as close as possible to the product. Allow as much space as possible between the product and devices that generate powerful high frequencies (high-frequency welders, high-frequency sewing machines, etc.) or surge.
- Use this product within the rated load and power supply.
- Make sure that the rated voltage is attained within two seconds of turning ON the power using a switch or relay contact. If the voltage is applied gradually, the power may not be reset or output malfunctions may occur.
- Make sure that the Temperature Controller has 30 minutes or more to warm up after turning ON the power before starting actual control operations to ensure the correct temperature display.
- A switch or circuit breaker must be provided close to the product. The switch or circuit breaker must be within easy reach of the operator, and must be marked as a disconnecting means for this unit.
- Do not use paint thinner or similar chemical to clean with. Use standard grade alcohol.
- Design the system (e.g., control panel) considering the 2 seconds of delay that the product's output to be set after power ON.
- The output may turn OFF when shifting to certain levels. Take this into consideration when performing control.
- The number of non-volatile memory write operations is limited. Therefore, use RAM write mode when frequently overwriting data during communications or other operations.
- Always touch a grounded piece of metal before touching the Temperature Controller to discharge static electricity from your body.

## E5CB

17. Control outputs (for driving SSR) that are voltage outputs are not isolated from the internal circuits. When using a grounded thermocouple, do not connect any of the control output terminals to ground. (Doing so may result in an unwanted circuit path, causing error in the measured temperature.)
18. Use suitable tools when taking the Temperature Controller apart for disposal. Sharp parts inside the Temperature Controller may cause injury.
19. Do not use the Temperature Controller if the front sheet is peeling off or torn.
20. Check the orientation of the connectors on the USB-Serial Conversion Cable before connecting the Cable. Do not force a connector if it does not connect smoothly. Using excessive force may damage the connector.
21. Do not place heavy object on the USB-Serial Conversion Cable, bend the cable past its natural bending radius, or pull on the cable with undue force.
22. Do not connect or disconnect the USB-Serial Conversion Cable while communications are in progress. Product faults or malfunction may occur.
23. Make sure that the Conversion Cable's metal components are not touching the external power terminals.
24. Do not touch the connectors on the USB-Serial Conversion Cable with wet hands. Electrical shock may result.
25. The computer may operate incorrectly. Do not rapidly and repeatedly insert and disconnect the USB connector on the USB-Serial Conversion Cable.
26. The personal computer requires time to recognize the cable connection after the USB connector is connected to the personal computer. This delay does not indicate failure. Check the COM port number before starting communications.
27. The USB-Serial Conversion Cable may malfunction. Do not connect to a personal computer through a USB hub.
28. For the power supply voltage input, use a commercial power supply with an AC input. Do not use the output from an inverter as the power supply. Depending on the output characteristics of the inverter, temperature increases in the product may cause smoke or fire damage even if the product has a specified output frequency of 50/60 Hz.
29. Make sure that the indicators on the Temperature Controller are operating properly. Depending on the application conditions, deterioration in the connectors and cable may be accelerated, and normal communications may become impossible. Perform periodic inspection and replacement.
30. When extending or connecting the thermocouple lead wire, be sure to use compensating wires that match the thermocouple types.
31. When extending or connecting the lead wire of the platinum resistance thermometer, be sure to use wires that have low resistance and keep the resistance of the three lead wires the same.
32. The USB-Serial Conversion Cable may malfunction. Do not extend the USB cable with an extension cable to connect to the personal computer.
33. Noise may enter on the USB-Serial Conversion Cable, possibly causing equipment malfunctions. Do not leave the USB-Serial Conversion Cable connected constantly to the equipment.

### Precautions for Correct Use

#### Service Life

1. Use the product within the following temperature and humidity ranges:  
 Temperature: -10 to 55°C (with no icing or condensation)  
 Humidity: 25% to 85%  
 If the product is installed inside a control board, the ambient temperature must be kept to under 55°C, including the temperature around the product.
2. The service life of electronic devices like Temperature Controllers is determined not only by the number of times the relay is switched but also by the service life of internal electronic components. Component service life is affected by the ambient temperature: the higher the temperature, the shorter the service life and, the lower the temperature, the longer the service life. Therefore, the service life can be extended by lowering the temperature of the Temperature Controller.

3. When two or more Temperature Controllers are mounted horizontally close to each other or vertically next to one another, the internal temperature will increase due to heat radiated by the Temperature Controllers and the service life will decrease. In such a case, use forced cooling by fans or other means of air ventilation to cool down the Temperature Controllers. When providing forced cooling, however, be careful not to cool down the terminals sections alone to avoid measurement errors.

### Measurement Accuracy

1. Mount the product so that it is horizontally level.
2. If the measurement accuracy is low, check to see if input shift has been set correctly.

### Waterproofing

The degree of protection is as shown below. Sections without any specification on their degree of protection or those with IP□0 are not waterproof.

Front panel: IP66

Rear case: IP20, Terminal section: IP00

### Operating Precautions

1. It takes approximately two seconds for the outputs to turn ON from after the power supply is turned ON. Due consideration must be given to this time when incorporating Temperature Controllers in a sequence circuit.
2. When starting operation after the Temperature Controller has warmed up, turn OFF the power and then turn it ON again at the same time as turning ON power for the load. (Instead of turning the Temperature Controller OFF and ON again, switching from STOP mode to RUN mode can also be used.)
3. Avoid using the Controller in places near a radio, television set, or wireless installing. These devices can cause radio disturbances which adversely affect the performance of the Controller.
4. When complying with EMC standards, the cable connecting the sensor to the TC or Pt input must be 30 m or less. If the cable length exceeds 30 m, compliance with EMC standards will not be possible.

### Mounting

#### Mounting to a Panel

For waterproof mounting, waterproof packing must be installed on the Controller. Waterproofing is not possible when group mounting several Controllers. Waterproof packing is not necessary when there is no need for the waterproofing function.

1. Insert the E5CB into the mounting hole in the panel.
2. Push the adapter from the terminals up to the panel, and temporarily fasten the E5CB.
3. Tighten the two fastening screws on the adapter. Alternately tighten the two screws little by little to maintain a balance. Tighten the screws to a torque of 0.29 to 0.39 N·m.

### Precautions when Wiring

- Separate input leads and power lines in order to prevent external noise.
- Use AWG24 (cross-sectional area: 0.205 mm<sup>2</sup>) to AWG14 (cross-sectional area: 2.081 mm<sup>2</sup>) shielded twisted-pair cable.
- Use crimp terminals when wiring the terminals.
- Use the suitable wiring material and crimp tools for crimp terminals.
- Tighten the terminal screws to a torque of between 0.74 and 0.90 N·m.



## Warranty and Application Considerations

### Read and Understand This Catalog

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

### Warranty and Limitations of Liability

#### WARRANTY

OMRON's exclusive warranty is that the products are free from defects in materials and workmanship for a period of one year (or other period if specified) from date of sale by OMRON.

OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, REGARDING NON-INFRINGEMENT, MERCHANTABILITY, OR FITNESS FOR PARTICULAR PURPOSE OF THE PRODUCTS. ANY BUYER OR USER ACKNOWLEDGES THAT THE BUYER OR USER ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE. OMRON DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED.

#### LIMITATIONS OF LIABILITY

OMRON SHALL NOT BE RESPONSIBLE FOR SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS, OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED ON CONTRACT, WARRANTY, NEGLIGENCE, OR STRICT LIABILITY.

In no event shall the responsibility of OMRON for any act exceed the individual price of the product on which liability is asserted. IN NO EVENT SHALL OMRON BE RESPONSIBLE FOR WARRANTY, REPAIR, OR OTHER CLAIMS REGARDING THE PRODUCTS UNLESS OMRON'S ANALYSIS CONFIRMS THAT THE PRODUCTS WERE PROPERLY HANDLED, STORED, INSTALLED, AND MAINTAINED AND NOT SUBJECT TO CONTAMINATION, ABUSE, MISUSE, OR INAPPROPRIATE MODIFICATION OR REPAIR.

### Application Considerations

#### SUITABILITY FOR USE

OMRON shall not be responsible for conformity with any standards, codes, or regulations that apply to the combination of products in the customer's application or use of the products.

Take all necessary steps to determine the suitability of the product for the systems, machines, and equipment with which it will be used.

Know and observe all prohibitions of use applicable to this product.

NEVER USE THE PRODUCTS FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCTS ARE PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

### Disclaimers

#### PERFORMANCE DATA

Performance data given in this catalog is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of OMRON's test conditions, and the users must correlate it to actual application requirements. Actual performance is subject to the OMRON *Warranty and Limitations of Liability*.

#### CHANGE IN SPECIFICATIONS

Product specifications and accessories may be changed at any time based on improvements and other reasons. Consult with your OMRON representative at any time to confirm actual specifications of purchased product.

#### DIMENSIONS AND WEIGHTS

Dimensions and weights are nominal and are not to be used for manufacturing purposes, even when tolerances are shown.

**OMRON Corporation** Industrial Automation Company  
Tokyo, JAPAN

Contact: [www.ia.omron.com](http://www.ia.omron.com)

#### Regional Headquarters

##### OMRON EUROPE B.V.

Wegalaan 67-69-2132 JD Hoofddorp  
The Netherlands  
Tel: (31)2356-81-300/Fax: (31)2356-81-388

##### OMRON ELECTRONICS LLC

One Commerce Drive Schaumburg,  
IL 60173-5302 U.S.A.  
Tel: (1) 847-843-7900/Fax: (1) 847-843-7787

##### OMRON ASIA PACIFIC PTE. LTD.

No. 438A Alexandra Road # 05-05/08 (Lobby 2),  
Alexandra Technopark,  
Singapore 119967  
Tel: (65) 6835-3011/Fax: (65) 6835-2711

##### OMRON (CHINA) CO., LTD.

Room 2211, Bank of China Tower,  
200 Yin Cheng Zhong Road,  
PuDong New Area, Shanghai, 200120, China  
Tel: (86) 21-5037-2222/Fax: (86) 21-5037-2200

Authorized Distributor:

© OMRON Corporation 2010 All Rights Reserved.

In the interest of product improvement, specifications are subject to change without notice.

CSM\_2\_2\_0911  
Cat. No. H172-E1-01




Printed in Japan  
1110

# MXH Heated Formwork





| Item no. | Weight kg |
|----------|-----------|
| 129132   | 233.000   |

**Heated Panel MXH 270 x 240**  
6.480 m<sup>2</sup>. Heated Panel for Panel MX 270 x 240.





|        |         |
|--------|---------|
| 129133 | 147.000 |
|--------|---------|

**Heated Panel MXH 270 x 120**  
3.240 m<sup>2</sup>. Heated Panel for Panel MX 270 x 120.



|        |         |
|--------|---------|
| 129370 | 119.000 |
|--------|---------|

**Extension Heated Panel MXH 120 x 240**  
2.880 m<sup>2</sup>. Extension Heated Panel MXH for Panel MX 120 x 240.





# MXH Heated Formwork





| Item no. | Weight kg |
|----------|-----------|
| 129375   | 73.400    |

**Extension Heated Panel MXH 120 x 120**  
 1.440 m<sup>2</sup>. Extension Heated Panel MXH for Panel MX 120 x 120.





|        |        |
|--------|--------|
| 129134 | 72.400 |
|--------|--------|

**Extension Heated Panel MXH 60 x 240**  
 1.440 m<sup>2</sup>. Extension Heated Panel MXH for Panel MX 60 x 240.





|        |        |
|--------|--------|
| 129135 | 44.000 |
|--------|--------|

**Extension Heated Panel MXH 60 x 120**  
 0.720 m<sup>2</sup>. Extension Heated Panel MXH for Panel MX 120 x 60.





|        |       |
|--------|-------|
| 117990 | 0.132 |
|--------|-------|

**Fixing Bolt M14 MXH**



|        |       |
|--------|-------|
| 129139 | 3.440 |
|--------|-------|




**Adapter Connector MXH**



# MXH Heated Formwork

| Item no. | Weight kg |
|----------|-----------|
| 129136   | 3.260     |



**Connector RS MXH**  
 For connecting push-pull props and kicker braces on MXH Panels.



|        |        |
|--------|--------|
| 129330 | 19.100 |
|--------|--------|

**Control Box MXH**

**Complete with**  
 1 pc. 129137 Control Box Connector MXH  
**Note**  
 Follow Instructions for Use!



Accessories

|        |       |
|--------|-------|
| 129137 | 5.590 |
|--------|-------|

**Control Box Connector MXH**

|        |       |
|--------|-------|
| 128874 | 0.755 |
|--------|-------|

**Connector Cable MXH**  
 Power supply cable for Control Box MXH to MXH Panel.



|        |       |
|--------|-------|
| 128875 | 0.450 |
|--------|-------|

**Connecting Cable MXH**  
 Power supply cable for connection between MXH Panels and MXH Extension Heated Panels.





# MXH Heated Formwork



| Item no. | Weight kg |
|----------|-----------|
| 129141   | 8.440     |

## Tie Holder MXH

Parking position of MX Anchors on MXH Panels.




|        |        |
|--------|--------|
| 117321 | 31.000 |
|--------|--------|

## Lifting Gear Combi MX

For transporting stacks of MAXIMO and TRIO Panels. For attaching Lifting Hook MAXIMO 1.5 t and Stacking Device MAXIMO.

### Note

Follow Instructions for Use!



|        |       |
|--------|-------|
| 115168 | 7.460 |
|--------|-------|

## Lifting Hook MAXIMO 1.5 t

For transporting MAXIMO and TRIO Panels.

### Note



Follow Instructions for Use!

### Technical Data

Permissible load-bearing capacity:

Steel elements 1.5 t

Alu elements 750 kg



|        |        |
|--------|--------|
| 117466 | 10.600 |
|--------|--------|



## Push-Pull Prop RS 210, galv.

Extension length  $l = 1.30 - 2.10$  m.

For aligning PERI Formwork Systems and precast concrete elements.

### Note

Permissible load see PERI Design Tables.





# MXH Heated Formwork

| Item no. | Weight kg |
|----------|-----------|
| 118238   | 12.100    |

**Push-Pull Prop RS 260, galv.**  
 Extension length  $l = 2.30 - 2.60$  m.  
 For aligning PERI Formwork Systems and precast concrete elements.



**Note**  
 Permissible load see PERI Design Tables.



|        |        |
|--------|--------|
| 117467 | 15.500 |
|--------|--------|

**Push-Pull Prop RS 300, galv.**  
 Extension length  $l = 1.90 - 3.00$  m.  
 For aligning PERI Formwork Systems and precast concrete elements.



**Note**  
 Permissible load see PERI Design Tables.



|        |        |
|--------|--------|
| 117468 | 23.000 |
|--------|--------|

**Push-Pull Prop RS 450, galv.**  
 Extension length  $l = 2.80 - 4.50$  m.  
 For aligning PERI Formwork Systems and precast concrete elements.



**Note**  
 Permissible load see PERI Design Tables.



|        |        |
|--------|--------|
| 117469 | 39.900 |
|--------|--------|

**Push-Pull Prop RS 650, galv.**  
 Extension length  $l = 4.30 - 6.50$  m.  
 For aligning PERI Formwork Systems and precast concrete elements.

**Note**  
 Permissible load see PERI Design Tables.







# MXH Heated Formwork



| Item no. | Weight kg |
|----------|-----------|
| 028990   | 115.000   |

**Push-Pull Prop RS 1000, galv.**  
 Extension length  $l = 6.40 - 10.00$  m.  
 For aligning PERI Formwork Systems.



**Note**  
 Permissible load see PERI Design Tables.



|        |         |
|--------|---------|
| 103800 | 271.000 |
|--------|---------|

**Push-Pull Prop RS 1400, galv.**  
 Extension length  $l = 6.40 - 14.00$  m.  
 For aligning PERI Formwork Systems.



**Note**  
 Permissible load see PERI Design Tables.  
 Chain can be operated from bottom.



|        |       |
|--------|-------|
| 126666 | 3.070 |
|--------|-------|

**Base Plate-3 for RS 210 - 1400**  
 For assembly of Push-Pull Props RS 210, 260, 300, 450, 650, 1000 and 1400.

**Complete with**  
 2 pc. 105400 Pin Ø 20 x 140, galv.  
 2 pc. 018060 Cotter Pin 4/1, galv.  
 1 pc. 113063 Bolt ISO 4014 M12 x 80-8.8, galv.  
 1 pc. 113064 Hex Nut ISO7042-M12-8-G, galv.





|        |       |
|--------|-------|
| 124777 | 0.210 |
|--------|-------|



Accessories  
**Anchor Bolt PERI 14/20 x 130**

# MXH Heated Formwork

| Item no. | Weight kg |  | Complete with  |
|----------|-----------|--|--|
| 102018   | 4.880     | <b>Base Plate-2 for RS 1000/1400, galv.</b><br>For assembly of Push-Pull Props RS 210, 260, 300, 450, 650, 1000, 1400 and Heavy Duty Spindles. | 2 pc. 105400 Pin Ø 20 x 140, galv.<br>2 pc. 018060 Cotter Pin 4/1, galv. |





|        |       |  |  |
|--------|-------|--|--|
| 117343 | 3.250 | <b>Base Plate-2 for RS 210 - 1400, galv.</b><br>For assembly of Push-Pull Props RS 210, 260, 300, 450, 650, 1000 and 1400. | <b>Complete with</b><br>2 pc. 105400 Pin Ø 20 x 140, galv.<br>2 pc. 018060 Cotter Pin 4/1, galv. |
|--------|-------|--|--|





Accessories

|        |        |   |   |
|--------|--------|---|---|
| 124777 | 0.210  | <b>Anchor Bolt PERI 14/20 x 130</b>   |   |
| 028010 | 17.900 | <b>Push-Pull Prop RSS I</b><br>Extension length l = 2.05 – 2.94 m.<br>For aligning PERI Formwork Systems. | <b>Note</b><br>Permissible load see PERI Design Tables. |



Accessories

|        |       |   |   |
|--------|-------|---|---|
| 113397 | 1.600 | <b>Spindle Handle RSS / AV</b>  |   |
| 113397 | 1.600 | <b>Spindle Handle RSS / AV</b><br>Spindle handle for screwing on Push-Pull-Props RSS I, RSS II and Kickers AV 210 and AV RSS III. | <b>Complete with</b><br>2 pc. 722342 Screw ISO 4017 M8 x 25-8.8, galv.<br>2 pc. 711071 Nut ISO 7042 M8-8, galv. |





# MXH Heated Formwork

| Item no. | Weight kg |
|----------|-----------|
| 028020   | 22.000    |

**Push-Pull Prop RSS II**  
 Extension length l = 2.91 – 3.80 m.  
 For aligning PERI Formwork Systems.

**Note**  
 Permissible load see PERI Design Tables.



Accessories



|        |       |
|--------|-------|
| 113397 | 1.600 |
|--------|-------|

**Spindle Handle RSS / AV**

|        |        |
|--------|--------|
| 028030 | 38.400 |
|--------|--------|

**Push-Pull Prop RSS III**  
 Extension length l = 4.60 – 6.00 m.  
 For aligning PERI Formwork Systems.



**Note**  
 Permissible load see PERI Design Tables.



|        |       |
|--------|-------|
| 106000 | 1.820 |
|--------|-------|

**Base Plate-2 for RSS, galv.**  
 For assembly of Push-Pull Props RSS.

**Complete with**  
 1 pc. 027170 Pin Ø 16 x 42, galv.  
 1 pc. 018060 Cotter Pin 4/1, galv.



Accessories

|        |       |
|--------|-------|
| 124777 | 0.210 |
|--------|-------|

**Anchor Bolt PERI 14/20 x 130**

# MXH Heated Formwork



| Item no. | Weight kg |
|----------|-----------|
| 057087   | 3.510     |
| 057088   | 4.200     |

**Kicker AV**  
**Kicker AV 82**  
**Kicker AV 111**  
 For aligning PERI Formwork Systems.

| min. L | max. L |
|--------|--------|
| 500    | 820    |
| 790    | 1110   |

**Complete with**  
 1 pc. 027170 Pin Ø 16 x 42, galv.  
 1 pc. 018060 Cotter Pin 4/1, galv.

**Note**  
 Permissible load see PERI Design Tables.





|        |       |
|--------|-------|
| 028110 | 4.850 |
|--------|-------|

**Kicker AV 140**  
 Extension length l = 1.08 – 1.40 m.  
 For aligning PERI Formwork Systems.

**Complete with**  
 1 pc. 027170 Pin Ø 16 x 42, galv.  
 1 pc. 018060 Cotter Pin 4/1, galv.

**Note**  
 Permissible load see PERI Design Tables.





|        |        |
|--------|--------|
| 108135 | 12.900 |
|--------|--------|

**Kicker AV 210**  
 Extension length l = 1.28 – 2.10 m.  
 For aligning PERI Formwork Systems.

**Complete with**  
 1 pc. 027170 Pin Ø 16 x 42, galv.  
 1 pc. 018060 Cotter Pin 4/1, galv.

**Note**  
 Permissible load see PERI Design Tables.



Accessories  
**Spindle Handle RSS / AV**

|        |       |
|--------|-------|
| 113397 | 1.600 |
|--------|-------|

# MXH Heated Formwork





| Item no. | Weight kg |
|----------|-----------|
| 028120   | 17.000    |

**Kicker AV RSS III**  
 Extension length l = 2.03 – 2.92 m.  
 For aligning PERI Formwork Systems.

**Complete with**  
 1 pc. 027170 Pin Ø 16 x 42, galv.  
 1 pc. 018060 Cotter Pin 4/1, galv.

**Note**  
 Permissible load see PERI Design Tables.





|        |       |
|--------|-------|
| 113397 | 1.600 |
|--------|-------|

Accessories  
**Spindle Handle RSS / AV**

|        |       |
|--------|-------|
| 028080 | 2.970 |
|--------|-------|

**Connector Kicker/Push-Pull Prop, galv.**  
 For connecting push-pull props and kicker braces to Main Beam HDT.



**Complete with**  
 1 pc. 027170 Pin Ø 16 x 42, galv.  
 1 pc. 018060 Cotter Pin 4/1, galv.




|        |       |
|--------|-------|
| 124777 | 0.210 |
|--------|-------|

**Anchor Bolt PERI 14/20 x 130**  
 For temporary fixation to reinforced concrete structures.

**Note**  
 See PERI Data Sheet!  
 Drilling Ø 14 mm.



# PERI International



## North America

- CA** Canada  
PERI Formwork Systems, Inc.  
[www.peri.ca](http://www.peri.ca)
- MX** Mexico  
PERI Cimbras y Andamios, S.A. de C.V.  
[www.peri.com.mx](http://www.peri.com.mx)
- PA** Panama  
PERI Panama Inc.  
[www.peri.com.pa](http://www.peri.com.pa)
- US** USA  
PERI Formwork Systems, Inc.  
[www.peri-usa.com](http://www.peri-usa.com)

## South America

- AR** Argentina  
PERI S.A.  
[www.peri.com.ar](http://www.peri.com.ar)
- BR** Brazil  
PERI Formas e Escoramentos Ltda.  
[www.peribrasil.com.br](http://www.peribrasil.com.br)
- CL** Chile  
PERI Chile Ltda.  
[www.peri.cl](http://www.peri.cl)
- CO** Colombia  
PERI S.A.S.  
[www.peri.com.co](http://www.peri.com.co)
- PE** Peru  
PERI Peruana S.A.C.  
[www.peri.com.pe](http://www.peri.com.pe)

## Africa

- AO** Angola  
Pericofragens, Lda.  
[www.peri.pt](http://www.peri.pt)
- DZ** Algeria  
S.A.R.L. PERI  
[www.peri.dz](http://www.peri.dz)
- EG** Egypt  
Egypt Branch Office  
[www.peri.com.eg](http://www.peri.com.eg)
- MA** Morocco  
PERI S.A.  
[www.peri.ma](http://www.peri.ma)
- MZ** Mozambique  
PERI (Pty.) Ltd.  
[www.peri.co.mz](http://www.peri.co.mz)
- NA** Namibia  
PERI (Pty.) Ltd.  
[www.peri.na](http://www.peri.na)
- NG** Nigeria  
PERI Nigeria Ltd.  
[www.peri.ng](http://www.peri.ng)
- TN** Tunisia  
PERI S.A.U.  
[www.peri.es](http://www.peri.es)
- TZ** Tanzania  
PERI Formwork and Scaffolding Ltd  
[www.peri.co.tz](http://www.peri.co.tz)
- ZA** South Africa  
PERI Formwork Scaffolding (Pty) Ltd  
[www.peri.co.za](http://www.peri.co.za)

## Asia

- AE** United Arab Emirates  
PERI (L.L.C.)  
[www.peri.ae](http://www.peri.ae)
- AZ** Azerbaijan  
PERI Representative Office  
[www.peri.com.tr](http://www.peri.com.tr)
- HK** Hong Kong  
PERI (Hong Kong) Limited  
[www.perihk.com](http://www.perihk.com)
- ID** Indonesia  
PT Beton Perkasa Wijaksana  
[www.betonperkasa.com](http://www.betonperkasa.com)
- IL** Israel  
PERI F.E. Ltd.  
[www.peri.co.il](http://www.peri.co.il)
- IN** India  
PERI (India) Pvt Ltd  
[www.peri.in](http://www.peri.in)
- IR** Iran  
PERI Pars. Ltd.  
[www.peri.ir](http://www.peri.ir)
- JO** Jordan  
PERI GmbH – Jordan  
[www.peri.com](http://www.peri.com)
- JP** Japan  
PERI Japan K.K.  
[www.peri.co.jp](http://www.peri.co.jp)
- KR** Korea  
PERI (Korea) Ltd.  
[www.perikorea.com](http://www.perikorea.com)
- KW** Kuwait  
PERI Kuwait W.L.L.  
[www.peri.com.kw](http://www.peri.com.kw)
- KZ** Kazakhstan  
TOO PERI Kazakhstan  
[www.peri.kz](http://www.peri.kz)
- LB** Lebanon  
PERI Lebanon Sarl  
[lebanon@peri.de](mailto:lebanon@peri.de)
- MY** Malaysia  
PERI Formwork Malaysia Sdn. Bhd.  
[www.perimalaysia.com](http://www.perimalaysia.com)
- OM** Oman  
PERI (L.L.C.)  
[www.peri.ae](http://www.peri.ae)
- PH** Philippines  
PERI-Asia Philippines, INC.  
[www.peri.com.ph](http://www.peri.com.ph)
- QA** Qatar  
PERI Qatar LLC  
[www.peri.qa](http://www.peri.qa)
- SA** Saudi Arabia  
PERI Saudi Arabia Ltd.  
[www.peri.com.sa](http://www.peri.com.sa)
- SG** Singapore  
PERI Asia Pte Ltd  
[www.periasia.com](http://www.periasia.com)
- TH** Thailand  
Peri (Thailand) Co., Ltd.  
[www.peri.co.th](http://www.peri.co.th)
- TR** Turkey  
PERI Kalıp ve İskeleleri  
[www.peri.com.tr](http://www.peri.com.tr)
- VN** Vietnam  
PERI ASIA PTE LTD  
[www.peri.com.vn](http://www.peri.com.vn)

**PERI**

**PERI GmbH**  
**Formwork Scaffolding Engineering**  
 Rudolf-Diesel-Strasse 19  
 89264 Weissenhorn  
 Germany  
 Tel. +49 (0)7309.950-0  
 Fax +49 (0)7309.951-0  
 info@peri.com  
 www.peri.com



## Oceania

**AU** Australia  
 PERI Australia Pty. Ltd.  
 www.periaus.com.au

**DK** Denmark  
 PERI Danmark A/S  
 www.peri.dk

**IT** Italy  
 PERI S.r.l.  
 www.peri.it

**SE** Sweden  
 PERI Sverige AB  
 www.peri.se

## Europe

**AL** Albania  
 PERI Kalip ve Iskeleleri  
 www.peri.com.tr

**EE** Estonia  
 PERI AS  
 www.peri.ee

**LT** Lithuania  
 PERI UAB  
 www.peri.lt

**SI** Slovenia  
 PERI oplate i skele d.o.o  
 www.peri.com.hr

**AT** Austria  
 PERI Ges.mbH  
 www.peri.at

**ES** Spain  
 PERI S.A.U.  
 www.peri.es

**LU** Luxembourg  
 N.V. PERI S.A.  
 www.peri.lu

**SK** Slovakia  
 PERI spol. s. r.o.  
 www.peri.sk

**BA** Bosnia and Herzegovina  
 PERI oplate i skele d.o.o  
 www.peri.com.hr

**FI** Finland  
 PERI Suomi Ltd. Oy  
 www.perisuomi.fi

**LV** Latvia  
 PERI SIA  
 www.peri-latvija.lv

**UA** Ukraine  
 TOW PERI  
 www.peri.ua

**BE** Belgium  
 PERI N.V.  
 www.peri.be

**FR** France  
 PERI S.A.S.  
 www.peri.fr

**NL** Netherlands  
 PERI b.v.  
 www.peri.nl

**NO** Norway  
 PERI Norge AS  
 www.peri.no

**BG** Bulgaria  
 PERI Bulgaria EOOD  
 www.peri.bg

**GB** United Kingdom  
 PERI Ltd.  
 www.peri.ltd.uk

**PL** Poland  
 PERI Polska Sp. z o.o.  
 www.peri.com.pl

**BY** Belorussia  
 IOOO PERI  
 www.peri.by

**GR** Greece  
 PERI Hellas Ltd.  
 www.perihellas.gr

**PT** Portugal  
 Pericofragens Lda.  
 www.peri.pt

**CH** Switzerland  
 PERI AG  
 www.peri.ch

**HR** Croatia  
 PERI oplate i skele d.o.o.  
 www.peri.com.hr

**RO** Romania  
 PERI România SRL  
 www.peri.ro

**CZ** Czech Republic  
 PERI spol. s r.o.  
 www.peri.cz

**HU** Hungary  
 PERI Kft.  
 www.peri.hu

**RS** Serbia  
 PERI oplate d.o.o.  
 www.peri.rs

**DE** Germany  
 PERI GmbH  
 www.peri.de

**IR** Ireland  
 Siteserv Access & Formwork  
 www.siteservaccess.ie

**RU** Russia  
 OOO PERI  
 www.peri.ru

**IS** Iceland  
 Armar ehf.  
 www.armor.is

The optimal System  
for every Project and  
every Requirement



Wall Formwork




Column Formwork



Slab Formwork



Climbing Systems



Bridge Formwork



Tunnel Formwork



Shoring Systems



Construction Scaffold



Facade Scaffold



Industrial Scaffold



Access



Protection Scaffold



Safety Systems



System-Independent  
Accessories



Services



**PERI GmbH**  
**Formwork Scaffolding Engineering**  
Rudolf-Diesel-Strasse 19  
89264 Weissenhorn  
Germany  
Tel. +49 (0)7309.950-0  
Fax +49 (0)7309.951-0  
info@peri.com  
www.peri.com

